

Item Image



## 84 EURO4

Sheer EuroFix Plates Satin Steel Double Plate c/w 4 EuroFix Apertures and Grid.

|                               |  |
|-------------------------------|--|
| Primary Range                 | Sheer                                    |
| Insert Type                   | EuroFix Apertured Plates                 |
| Plate Finish                  | Satin Steel                              |
| Frame Finish                  |  |
| Switch Colour                 |  |
| Body & Switch Trim            |  |
| Height                        | Double = 86mm                            |
| Width                         | Double = 146mm                           |
| Depth                         | Double = 1.5mm                           |
| Fixing Hole Centres           | Box Fixing = 120.6mmBox Fixing = 120.6mm |
| Minimum Wall Box Depth        | 35mm                                     |
| Wattage                       |  |
| Switched Poles                | n/a                                      |
| Current Rating                |  |
| Voltage                       |  |
| Max load                      |  |
| Contact Gap Minimum           | n/a                                      |
| Terminal Capacity 1           |  |
| Terminal Capacity 2           |  |
| Terminal Capacity 3           |  |
| Terminal Capacity 4           |  |
| Terminal Capacity 5           |  |
| Earth Terminal Capacity 1     | 5 x 1mm <sup>2</sup>                     |
| Earth Terminal Capacity 2     | 4 x 1.5mm <sup>2</sup>                   |
| Earth Terminal Capacity 3     | 3 x 2.5mm <sup>2</sup>                   |
| Earth Terminal Capacity 4     | 1 x 4mm <sup>2</sup> Multi-Strand        |
| Earth Terminal Capacity 5     | 1 x 6mm <sup>2</sup>                     |
| Product Class 1               | Face plate must be earthed               |
| Ambient Operating Temperature |  |
| Recommended Location          | Indoor use only                          |
| Standard/Approval             |  |
| Patents and Trademarks        | Trade Mark No. 2296586                   |

|  |  |   |
|--|--|---|
| All products listed conform to current British or European standards and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.                 | It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.                  | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at August 2012<br>E&OE   |

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK  
T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com  
www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary)  
Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire  
Registered in London No. 941624 • VAT Registration No. 222 6607 84

