## **STAINLESS STEEL ROLLER BALL CABLE TIES**

- Minimum loop tensile strength 4.6mm wide = 44kg
- Minimum loop tensile strength 7.9mm wide = 110kg
- High quality 316 grade stainless steel cable ties
- Dimensions A, D & E: Nominal Dimensions B & C: +-0.4mm



Part Number	А	В	С	D	E	Bundle Dia. Max.	Pack Qty
QSST150S	150mm	4.6mm	0.25mm	6.4mm	4mm	35mm	100
QSST200S	200mm	4.6mm	0.25mm	6.4mm	4mm	50mm	100
QSST300S	300mm	4.6mm	0.25mm	6.4mm	4mm	83mm	100
QSST360S	360mm	4.6mm	0.25mm	6.4mm	4mm	100mm	100
QSST520S	520mm	4.6mm	0.25mm	6.4mm	4mm	150mm	100
QSST300LH	300mm	7.9mm	0.25mm	10.6mm	5.4mm	83mm	100
QSST360LH	360mm	7.9mm	0.25mm	10.6mm	5.4mm	100mm	100
QSST520LH	520mm	7.9mm	0.25mm	10.6mm	5.4mm	150mm	50
QSST840LH	840mm	7.9mm	0.25mm	10.6mm	5.4mm	250mm	50

# **STAINLESS STEEL MOUNTS**

#### Stainless Steel Cable Tie Mount

- Stainless steel cable tie mounts with M4 or M6 fixing hole, pack of 50
- Can be used with cable ties up to 10mm wide
- For indoor and outdoor use, fully weather, UV and fire resistant
- High quality 316 grade stainless steel

Description	Dimensions	Fixing Dia.	Max. Tie Width	Pack Qty
Stainless Steel Cable Tie Mount M4	15 x 29.20 x 5mm	4.2mm	10mm	50
Stainless Steel Cable Tie Mount M6	15 x 29.20 x 5mm	6.2mm	10mm	50

### **MASONRY SCREW**

- M4.8 x 40MM Masonry Screw
- Use to fasten various fixtures directly to drywall, wood, concrete, sand / lime stone or brickwork
- No plug needed

Part Number

QSSTM-4

QSSTM-6

Part Number	Description	Length	Thread Dia.	Pack Qty
QMA48-40	4.8 x 40mm Masonry Fixing Screw - Blue	40mm	4.8mm	100

### **FIRE SAFE METAL CABLE CLIPS**

- Long nail for good pull out value
- Thick steel nail prevents snapping
- Stress crack resistant
- High grade steel construction for high temperature fire rated installations

T	

Part Number	Description
QMC25	1 - 2.5mm <sup>2</sup> Metal T&E Cable Clips
QMC6	4 - 6mm <sup>2</sup> Metal T&E Cable Clips
QMC25GY	1 - 2.5mm <sup>2</sup> Metal LSF T&E Cable Clips - Grey
QMC6GY	4 - 6mm <sup>2</sup> Metal LSF T&E Cable Clips - Grey

## **FIRE RESISTANT SEALANTS & FOAM**

- ZFPAR310W For indoor use only
- ZFPSIL310W For outdoor use only
- Expanding Foam fire resistant for up to 240 minutes in combination with other products
- Both Sealants fire resistant for up to 4 hours
- ZFPAR310W Can be applied separately in joints up to 20mm wide
- ZFPSIL310W Can be applied in joints up to 30mm wide

Part Number	Description
ZFPACR310W	Fire Resistant Acrylic Sealant - 310ml
ZFPSIL310W	Fire Retardant Silicone Sealant - 310ml
SXFLAMEFF700HAND	Fire Retardant Hand Held Expanding Foam

UNI**CRIMP** 4



Suitable Cable Size	Pack Qty
1mm <sup>2</sup> - 2.5mm <sup>2</sup> T&E	100
4mm <sup>2</sup> - 6mm <sup>2</sup> T&E	100
1mm <sup>2</sup> - 2.5mm <sup>2</sup> T&E	100
4mm <sup>2</sup> - 6mm <sup>2</sup> T&E	100



Pack Qty
1
1
1

**Q**-FIRE

5

