

Technical Specification

Product Code: VPSC205BK Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Outlet & Neons





Representative Image

General Information

146mm (W) x 88mm (H) x 8mm (D) Dimensions

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Satin Chrome

Insert & Gasket Colour Black

> Materials Front Plate: Stainless Steel

Insert, Switch & Rear Housing: Urea

Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

> Load Rating 45A

Plate Fixing Centres 120.6mm

Terminal Size 6mmø **Terminal Torque** 2.5Nm **Terminal Capacity** 1 x 16mm²

Double Pole Yes Twin Earth Terminals Yes

Neon Indicator Yes (Red)

Ingress Protection IP20

Back Box Depth 35mm Minimum **Operational Temperature** -5°C to +40°C 10 Years

Warranty

Standards BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification













SCP323BK

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com