



Technical Specification

Product Code: VPSB424

Description: 10AX 4 Gang 2 Way Toggle Plate Switch





Representative Image

146mm (W) x 88mm (H) x 8mm (D) 149mm (W) x 91mm (H) x 9mm (D)
149mm (W) x 91mm (H) x 9mm (D)
Victorian Satin Brass
Supplied With Both Black & White Gasket
Polished Brass
Front Plate: Stainless Steel Switch Front & Nut: Cast Zinc Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon
250V~ 50Hz
10AX (Suitable for Inductive Loads)
120.6mm
4.9mm x 4.1mm
1.2Nm
4 x 1.5mm ² or 2 x 2.5mm ²
Yes
IP20
25mm Minimum
-5°C to +40°C
10 Years
BS EN 60669-1:1999 +A1:2002 +A2:2008
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125BR for polished brass finish.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 Rev.1. Errors & Omissions excluded ecification is subject to change without notice