



## **Technical Specification**

**General Information** 

## Product Code: VPSS065BK

Description: Single Non-Isolated Coaxial Outlet





Representative Image

| Dimensions              | 88mm (W) x 88mm (H) x 8mm (D)  |
|-------------------------|--|
| Dimensions With Gasket  | 91mm (W) x 91mm (H) x 9mm (D)  |
| Plate Design & Finish   | Victorian Stainless Steel  |
| Insert & Gasket Colour  | Black  |
| Materials               | Front Plate: Stainless Steel<br>Insert: Urea<br>Earth Plate: Mild Steel<br>Terminals: Brass<br>Gasket: Nylon   |
| Plate Fixing Centres    | 60.3mm   |
| Isolated                | Non-isolated (Direct connection to aerial where 2 way signal is required)  |
| Shielded                | No   |
| Ingress Protection      | IP20   |
| Back Box Depth          | 16mm Minimum   |
| Operational Temperature | -5°C to +40°C  |
| Warranty                | 10 Years   |
| Additional Information  | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.<br>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.<br>Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required. |