

## 

Page Errors & Omiss ecification is subject to change

## **Technical Specification**

## Product Code: VPSS100WH

Description: 115V/230V Dual Voltage Shaver Socket Outlet





## **General Information**

Dimensions   88mm (W) x 146mm (H) x 8mm (D)     Dimensions With Gasket   91mm (W) x 149mm (H) x 9mm (D)     Plate Design & Finish   Victorian Stainless Steel     Insert & Gasket Colour   While     Materials   Front Prate: Stainless Steel     Insert & Rear Housing: Urea Terminals: Grass   Terminals: Craws: Steel & Yellow Passivated Contacts: Silver Contact's Silver Contet Silver Silver Silver S		
Plate Design & Finish Victorian Stainless Steel   Insert & Gasket Colour White   Materials Front Plate: Stainless Steel   Insert & Rear Housing: Urea Terminals: Breas   Terminals: Stress: Steel & Yellow Passivated Contracts: Silver fon-lay" Copper / Brass   Internal Busbars: Pormed Pressed Brass Earth Strap: Mild Steel   Gasket: Nylon Additional   Maximum Voltage 20V - 50/60Hz   Load Rating 20Va at 230V or 115V   Plate Fixing Centres 120.6mm (Vertical Fixing)   Terminal Torque 0.5Nm   Terminal Torque 0.5Nm   Terminal Stress: PTC Resetable Fuse   Product Markings Shavers Only. 230V~, 115V~   Fuse PTC Resetable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to ±40°C   Warranty 10 Years   Standards BS EN 61558-1:2005 ± A1:2009   BS EN 61558-1:2005 ± A1:2009 BS EN 61558-2-5:2010	Dimensions	88mm (W) x 146mm (H) x 8mm (D)
Insert & Gasket Colour White   Materials Front Plats: Stainless Steel Insert & Rear Housing: Urea Terminals: Brass   Terminal Screws: Steel & Yellow Passivated Contacts: Silver 'on-lay' Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon   Maximum Voltage 240V~50/60Hz   Load Rating 20Va at 230V or 115V   Plate Fridge Offman 20mm (Vertical Fixing)   Terminal Strap: Mild Steel 3.5mmo   Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²   Tominal Torque 0.5Nm   Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²   Twin Earth Terminals Yes   Product Markings Shavers Only. 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 20Vo at 153V and meests SE EN 61558-2-5:2010	Dimensions With Gasket	91mm (W) x 149mm (H) x 9mm (D)
MaterialsFront Plate: Stainless Steel Insert & Rear Housing: Urea Terminals: Brass Terminal: Brass Terminal: Strass: Steel & Vellow Passivated Contacts: Silver 'on-lay" Copper / Brass Earth Stray: Mild Steel Gasket: NylonMaximum Voltage240V- 50/60Hz Load Rating2004 at 230V or 115V Plate Fixing CentresPlate Fixing Centres120 6mm (Vertical Fixing) Terminal Capacity2.5mmaTerminal Torque0.5Nm 0.5NmTerminal Capacity2 x 1.5mm² or 1 x 2.5mm² Twin Earth Terminal Back Box Depth47mm 47mmTerminationYes Product MarkingsShavers Only. 230V~, 115V~ FuseBack Box Depth47mm 47mm TerminationProduct MarkingsStandardsBS N 61558-1:2005 + A1:2009 BS EN 61558-2:5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased diow, PTC resettable fuses are designed to limit unsafe current while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. En	Plate Design & Finish	Victorian Stainless Steel
Insert & Rear Housing: Urea Terminal: Brass Terminal: Strass Terminal: Strass Terminal Strass: Stell & Yellow Passivated Contacts: Stilver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: NylonMaximum Voltage Load Rating20Va at 230V or 115VPlate Fixing Centres Terminal Size 3.5mme120.6mm (Vertical Fixing) 3.5mmeTerminal Size Terminal Torque Terminal Torque 0.5Nm3.5mmeTerminal Capacity Product Markings2x 1.5mm² or 1 x 2.5mm² Twin Earth Termination Product Markings Shavers Only, 230V~, 115V~ Fuse Product MarkingsYes Stavers Only, 230V~, 115V~ Fuse Product Markings Stavers Only, 230V~, 115V~ Fuse Product MarkingsStavers Only, 230V~, 115V~ Stavers Only, 230V~, 115V~ Fuse StandardsStandards BS EN 61558-1:2005+A1:2009 BS EN 61558-2:5:2010BS EN 61558-2:5:2010Additional Information PTC resettable fuses incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010 making it safe for use in a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses increase resistance as temperature increases due to increased down. PTC resettable fuses increase resistance as temperature increases due to increased down. PTC resettable fuses increase resistance as temperature increases due to increased end temperature returns to a safe level. Ensure that the mains supply is isolated before commercing installation and refer to the circuit diagram wit	Insert & Gasket Colour	White
Load Rating20Va at 230V or 115VPlate Fixing Centres120.6mm (Vertical Fixing)Terminal Size3.5mmeTerminal Torque0.5NmTerminal Torque0.5NmTerminal Torque0.5NmTerminal Capacity2 x 1.5mm² or 1 x 2.5mm²Twin Earth TerminalsYesProduct MarkingsShavers Only, 230V~, 115V~FusePTC Resettable FuseIngress ProtectionIP21Back Box Depth47mmTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resetable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature forcus tileagram with the relevant product.	Materials	Insert & Rear Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Plate Fixing Centres 120.6mm (Vertical Fixing)   Terminal Size 3.5mmø   Terminal Torque 0.5Nm   Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²   Twin Earth Terminals Yes   Product Markings Shavers Only, 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005 + A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Maximum Voltage	240V~ 50/60Hz
Terminal Size 3.5mm/   Terminal Torque 0.5Nm   Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²   Twin Earth Terminals Yes   Product Markings Shavers Only, 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shave outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increases flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	•	20Va at 230V or 115V
Terminal Torque 0.5Nm   Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²   Twin Earth Terminals Yes   Product Markings Shavers Only, 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005 +A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incroprorate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Plate Fixing Centres	120.6mm (Vertical Fixing)
Terminal Capacity2 x 1.5mm² or 1 x 2.5mm²Twin Earth TerminalsYesProduct MarkingsShavers Only, 230V~, 115V~FusePTC Resettable FuseIngress ProtectionIP21Back Box Depth47mmTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
Twin Earth Terminals Yes   Product Markings Shavers Only, 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
Product Markings Shavers Only, 230V~, 115V~   Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Terminal Capacity	2 x 1.5mm <sup>2</sup> or 1 x 2.5mm <sup>2</sup>
Fuse PTC Resettable Fuse   Ingress Protection IP21   Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
Ingress ProtectionIP21Back Box Depth47mmTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Product Markings	Shavers Only, 230V~, 115V~
Back Box Depth 47mm   Termination Type Screw   Operational Temperature -5°C to +40°C   Warranty 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2:5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Fuse	
Termination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	-	IP21
Operational Temperature Warranty -5°C to +40°C   10 Years 10 Years   Standards BS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		47mm
Warranty10 YearsStandardsBS EN 61558-1:2005+A1:2009 BS EN 61558-2-5:2010Additional InformationThis outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		Screw
Standards BS EN 61558-1:2005 + A1:2009 BS EN 61558-2-5:2010   Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Operational Temperature	-5°C to +40°C
Additional Information This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Warranty	10 Years
CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Standards	
	Additional Information	CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com