

5 Year Warranty

L70 50,000hrs

Triac dimmable as
standard

White, Matt White,
Polished Chrome &
Satin Nickel bezel
finish options



works with

.control



Triac Inline Dimmer
See pg.41



Smart Rotary Dimmer
See pg.35



AU-A6PRO



AU-A6PRO

(H) 100mm Height
(OD) 85mm Overall (Ø)

AU-A62PRO

(H) 105mm Height
(OD) 95mm Overall (Ø)

A6TMPRO

LED Fixed/Adjustable Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

Delivering up to 117lm/W

Slim, interchangeable IP65 bezels (fixed version) providing a sleek finish

IP20 bezel included for adjustable version

Unique RapidWire connection system

60° beam angle for uniform light distribution

Fibre based insulation coverable - up to 300mm

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings[†]



Fixed IP65



Adjustable

Fire Rated Downlights



AIR leakage
(excluding
adjustable)

Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]
A6PROTM Triac Dimmable Fixed (IP65 when used with IP65 Bezel)						
AU-A6PRO/30	6W	3000K	600lm	100	60°	70mm
AU-A6PRO/40	6W	4000K	620lm	103	60°	70mm
A6PROTM Triac Dimmable Adjustable						
AU-A62PRO*/30	6W	3000K	680lm	113	60°	80mm
AU-A62PRO*/40	6W	4000K	700lm	117	60°	80mm

Bezel Options

AU-BZA6*

A6TM PRO/A6TM Fixed IP65 Aluminium Downlight Bezel

AU-AP86*

Fire Rated Aluminium Adaptor Plate Fixed 85-145mm

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.

[†]Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262

