

3 Year Warranty

L70 25,000hrs

Triac dimmable as standard

Emergency option


White, Matt White, Polished
Chrome & Satin Nickel
bezel finish options





works with

.control

Smart Rotary Dimmer
See pg.35



Triac Inline Dimmer
See pg.41



EN-DE5

(H) 69mm Height
(OD) 78mm Overall (Ø)

EN-DE52

(H) 90mm Height
(OD) 88mm Overall (Ø)

E5™

LED Fixed/Adjustable Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

Sparkling, low glare, multifaceted EnFiniti™ lens

Delivering up to 98lm/W

Slim, interchangeable IP65 bezels (fixed version) provide a sleek finish

IP20 bezel included for adjustable

Integrated driver with new push fit loop in/out terminals suitable for use with solid or stranded cable for easy installation

Fibre based insulation coverable - up to 300mm

60° beam angle for uniform light distribution

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings†



Fixed IP65



Adjustable



AIR leakage
(excluding
adjustable)

| Cat. No. | Watts | Colour | Lumens | lm/W | Beam | Cutout [Ø] |
|----------|-------|--------|--------|------|------|------------|
|----------|-------|--------|--------|------|------|------------|

E5™ Triac Dimmable Fixed (IP65 when used with IP65 Bezel)

| | | | | | | |
|-----------|------|-------|-------|----|-----|------|
| EN-DE5/30 | 4.5W | 3000K | 400lm | 89 | 60° | 65mm |
|-----------|------|-------|-------|----|-----|------|

| | | | | | | |
|-----------|------|-------|-------|----|-----|------|
| EN-DE5/40 | 4.5W | 4000K | 420lm | 93 | 60° | 65mm |
|-----------|------|-------|-------|----|-----|------|

E5™ Triac Dimmable Adjustable

| | | | | | | |
|-------------|------|-------|-------|----|-----|------|
| EN-DE52*/30 | 4.5W | 3000K | 420lm | 93 | 60° | 75mm |
|-------------|------|-------|-------|----|-----|------|

| | | | | | | |
|-------------|------|-------|-------|----|-----|------|
| EN-DE52*/40 | 4.5W | 4000K | 440lm | 98 | 60° | 75mm |
|-------------|------|-------|-------|----|-----|------|

Accessories

EN-BZE5* E5™ Fixed IP65 Aluminium Downlight Bezel

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.
3 hour Emergency pack AU-FRLM10EM available.

†Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262

