

5 Year Warranty

White, Matt White, Polished  
Chrome & Satin Nickel  
bezel finish options



works with


.light

Smart  
Tuneable GU10  
See pg.27



.control



Dimmable  
Standard GU10  
**PLUS**  
Triac Inline Dimmer  
See pg.41



**OR**  
Smart Rotary Dimmer  
See pg.35



Non-Dimmable  
Standard GU10  
**PLUS**  
On/Off Relay  
See pg.47



**EN-DLM981X**

(H) 107mm Height  
(OD) 90mm Overall (Ø)

**EN-DLM982X**

(H) 120mm Height  
(OD) 102mm Overall (Ø)

**EFD<sup>TM</sup> PRO**

**GU10 Professional Fixed/Adjustable  
Fire Rated Downlights**

make smart with



See pg.256-258 for compatibility table

Interchangeable bezels for fixed version use EN-DLM981X & EN-BZ91

Interchangeable bezels for adjustable version use EN-DLM982X & EN-BZ92

Interchangeable bezels for IP65 rated version use EN-DLM981X & EN-BZ93

Fitted with push-fit terminal block for faster installation

Fibre based insulation coverable - up to 300mm (LED lamps only)

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings\*

**Smart**  
Lamp options  
See pg.27



**Standard**  
Lamp options  
See pg.113



See luminaire lamp compatibility on pg.259



Fixed



Adjustable



Fixed IP65



AIR leakage  
(excluding  
adjustable)

Cat. No.	Input	Horz. Adj.	Cutout (Ø)
<b>Fixed/IP65</b>			
<b>EN-DLM981X</b>	240V	-	75mm
<b>Adjustable</b>			
<b>EN-DLM982X</b>	240V	20°	85mm
<b>Bezels</b>			
<b>EN-BZ91*</b>	EFD <sup>TM</sup> PRO 90mm Fixed Aluminium Downlight Bezel		
<b>EN-BZ92*</b>	EFD <sup>TM</sup> PRO 102mm Adjustable Aluminium Downlight Bezel		
<b>EN-BZ93*</b>	EFD <sup>TM</sup> PRO 90mm IP65 Aluminium Downlight Bezel		

\*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.  
Lamp not included

\*Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262

