

5 Year Warranty

L70 50,000hrs

1-10V & DALI dimmable options

Emergency option

White finish



works with

.control



1-10V Inline Dimmer
See pg.45

1-10V

On/Off Relay
See pg.47

16 A

EN-SF1560



Single & Twin 1200mm

(L) 1188mm Length
(W) 208mm Width
(H) 70mm Height

Single & Twin 1500mm

(L) 1488mm Length
(W) 208mm Width
(H) 70mm Height

Single 1800mm

(L) 1788mm Length
(W) 208mm Width
(H) 70mm Height

PrincetonTM PRO

Surface Mounted LED Linear

make smart with



See pg.256-258 for compatibility table

Up to 50% savings compared to fluorescent fittings

Steel housing and high quality polycarbonate diffuser

Delivering 110lm/W

IK06 rated impact resistance

Matches footprint of fluorescent - perfect for retrofitting

Standard version fitted with push-fit terminal block for even faster installation

Multiple BESA mounting points (matches traditional fluorescent)

Uniform light distribution eliminates hot spots



Linears

Cat. No.	Type	Watts	Colour	Lumens	lm/W	Beam	Length (ft)
Single							
EN-SF1220*/40	Non-Dim	20W	4000K	2200lm	110	110°	4
EN-SF1530*/40	Non-Dim	30W	4000K	3300lm	110	110°	5
EN-SF1840*/40	Non-Dim	40W	4000K	4400lm	110	110°	6
Twin							
EN-SF1240*/40	Non-Dim	40W	4000K	4400lm	110	110°	4
EN-SF1560*/40	Non-Dim	60W	4000K	6600lm	110	110°	5

*Add suffix **EM** for Emergency, **DA** for DALI or **V** for 1-10V dimmable options

