

Helius™

IP65 COB Floodlights

make smart with

 See pg.256-258 for compatibility table

- Die-cast aluminium housing
- Durable high quality paint
- Tempered glass provides excellent protection
- IP65 rated
- IK08 rated impact resistance
- Pre-wired with 800mm of cable
- Warning Note: Not suitable for post top mounting

3 Year Warranty
 L70 25,000hrs
 Black finish

make smart with




works with

.control

 On/Off Relay
 See pg.47



EN-FL30A



EN-FL10A

(H) 135mm Height
 (W) 115mm Width
 (D) 40mm Depth
 (BL) 85mm Bracket Length
 (BW) 102mm Bracket Width

EN-FL30A

(H) 230mm Height
 (W) 195mm Width
 (D) 60mm Depth
 (BL) 150mm Bracket Length
 (BW) 180mm Bracket Width

EN-FL50A

(H) 285mm Height
 (W) 240mm Width
 (D) 70mm Depth
 (BL) 188mm Bracket Length
 (BW) 212mm Bracket Width

Cat. No.	Watts	Colour	Lumens	lm/W
Non-Dimmable				
EN-FL10A/40	10W	4000K	750lm	75
EN-FL30A/40	30W	4000K	2250lm	75
EN-FL50A/40	50W	4000K	3750lm	75

