

## **Technical Specification**



Product Code: VPCH535WH Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet





Representative Image

## **General Information**

Plate Design & Finish Victorian Polished Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup> or 2 x 4mm<sup>2</sup>

Double Pole Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS 1363-2: 2016 +A1: 2018

**Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.