



Single colour flexible LED strip with 3M™ self adhesive backing

Cut points every 50mm for maximum flexibility

Beam angle of 120° and 17mm between LEDs, 60 LEDs per metre

Voltage drop of 4V per 10m and maximum run of 10m

For runs over 10m individual lengths should be connected in parallel

Reel length 30m



Cat. No.	Watts/m	No. of LEDs/m	Colour	lm/m
EN-ST100/30	4.8W	60	3000K	480lm
EN-ST100/40	4.8W	60	4000K	515lm
EN-ST100/60	4.8W	60	6300K	540lm
EN-ST100/BLU	4.8W	60	Blue	-

Accessories

EN-ST100A LEDLine™ PRO Single Colour Strip Connector EN-ST100B LEDLine™ PRO Single Colour Wired Strip Connector

LEDLine™ PRO Single Colour Inter-Connection Strip Connector EN-ST100C

3 Year Warranty

L70 35,000hrs

3000K, 4000K, 6300K & Blue colour options





.control



12/24V Inline Controller see pg.43



On/Off Relay see pg.47

EN-ST100A



EN-ST100B



EN-ST100C



Cat. No.	Description	Metres per driver
LED Drivers		
AU-LED1012CV	10W Non-Dimmable 12V Constant Voltage Driver	1m
AU-LED2512CV	25W Non-Dimmable 12V Constant Voltage Driver	5m
EN-LED7512	75W Non-Dimmable 12V Constant Voltage Driver	10m

75W Triac Dimmable 12V Constant Voltage Driver

10m

For alternative lengths see pg.245



EN-LEDD7512





