

Orbital™

IP66 Round/Eyelid LED Bulkheads



- Polycarbonate body and diffuser
- Rear entry access wiring compartment allows for easy installation
- Separate 20mm conduit side entry
- Delivering up to 80lm/W
- IP66 rated
- IK10 rated impact resistance
- Adjustable hold time 5 seconds to 10 minutes for microwave option
- Adjustable light detector for microwave option
- For ambient temperatures from -25° C to 40° C



IP66 Round

Eyelid Accessory

Microwave version
detection range

Cat. No.	Watts	Colour	Lumens	lm/W
Non-Dimmable				
EN-BH15*/40†	15W	4000K	1150lm	77
EN-BH15*/40EM	17W	4000K	1150lm	68
EN-BH25*/40†	25W	4000K	1800lm	72
EN-BH25*/40EM	27W	4000K	1800lm	67
NEW EN-BH35*/40†	35W	4000K	2800lm	80
NEW EN-BH35*/40EM	37W	4000K	2800lm	76

Accessories

EN-BZE15W	Orbital™ 300mm Eyelid Bezel Accessory for EN-BH15 - White
EN-BZE15BLK	Orbital™ 300mm Eyelid Bezel Accessory for EN-BH15 - Black
EN-BZE25W	Orbital™ 360mm Eyelid Bezel Accessory for EN-BH25 - White
EN-BZE25BLK	Orbital™ 360mm Eyelid Bezel Accessory for EN-BH25 - Black
NEW EN-BZE35W	Orbital™ 420mm Eyelid Bezel Accessory for EN-BH35 - White
NEW EN-BZE35BLK	Orbital™ 420mm Eyelid Bezel Accessory for EN-BH35 - Black

*Add suffix **W** or **BLK** for White or Black finishes

†Add suffix **MS** for Microwave Sensor

EN-BH25 27W EMMS (Emergency & Microwave Sensor) available to special order



3 Year Warranty

L70 25,000hrs

Microwave sensing option

Emergency option

Black or White finish options





works with

.control



On/Off Relay
See pg.47

EN-BH15



EN-BH15

(OD) 300mm Overall Ø
(P) 95mm Projection

EN-BH25

(OD) 360mm Overall Ø
(P) 105mm Projection

EN-BH35

(OD) 420mm Overall Ø
(P) 112mm Projection