



MAGDUOSSLP Sounder Strobe for MAGDUO – Low Profile

MAGDUOSS Sounder Strobe for MAGDUO – Domed



- Complete with 3 sounder modes and LED strobe
- Volume level adjustment
- Built-in End of Line function

- Low profile design
- Device wiring base included

Dimensions

Diameter	105mm
Depth	45mm (Low Profile) / 62mm (Domed)
Flush Depth Protruding	34 mm
Surface Depth	62 mm

Temperature Range

Operating Temperature	-10°C to +50°C
-----------------------	----------------

Voltage Ranges

DC Output from Mains Powered Panel	25.5 to 35V DC
DC Output from Battery Powered Panel	20 to 26V DC

Operating Current (Typical)

Quiescent	223 uA
End of line ON if applicable (in addition to Quiescent)	198 uA
Alarm Sounding – Sounder High	23.5 mA
Alarm Sounding – Sounder Low	15 mA
Beacon	5.5 mA

Volume Level (@ 1m anechoic, Dual Tone)

Sounder High	90+ dB(A)
Sounder Low	65+ dB(A)

Device Loading Units

Max Device Loading Units per Zone	160 DLU
Sounder High	54.0 DLU
Sounder Low	33.0 DLU
Beacon	33.0 DLU

LED Operation

EOL indication	5 second interval
----------------	-------------------

Beacon Operation

Period	1
Flash Duration	15 ms

Ingress Protection

IP Rating	IP 21C
-----------	--------