

# Nylon Cable Cleats – 12A

Black Polypropylene

1

## WRAPAROUND CABLE CLEAT

Single fixing provides a simple but strong means of securing cables.

UV resistant polypropylene.

2

## TCC TWO HOLE CLEAT

Designed to fit cable 50mm to 105mm diameter high strength and designed to be easily stacked to save space.

1



2



## S.W.A. Cables Copper Conductors 600/1000V to BS6346

Guide only, please check diameter of cable before ordering.

| Cable size | Core  |       |       |       |     |      |     |      |      |      |
|------------|-------|-------|-------|-------|-----|------|-----|------|------|------|
|            | 1     | 2     | 3     | 4     | 5   | 7    | 10  | 12   | 19   | 27   |
| 1.5        |       | CC5   | CC5   | CC6   | CC6 | CC6  | CC8 | CC8  | CC9  | CC11 |
| 2.5        |       | CC6   | CC6   | CC6   | CC6 | CC7  | CC9 | CC9  | CC11 | CC12 |
| 4.0        |       | CC6   | CC7   | CC7   | CC8 | CC8  | CC8 | CC11 |      |      |
| 6.0        |       | CC7   | CC8   | CC8   | CC8 | CC9  |     |      |      |      |
| 10.0       |       | CC8   | CC9   | CC9   | CC9 | CC10 |     |      |      |      |
| 16.0       |       | CC9   | CC10  | CC11  |     |      |     |      |      |      |
| 25.0       |       | CC11  | CC12  | CC12  |     |      |     |      |      |      |
| 35.0       |       | CC11  | CC12  | CC14  |     |      |     |      |      |      |
| 50.0       | CC8   | CC12  | CC12  | CC14  |     |      |     |      |      |      |
| 70.0       | CC9   | CC12  | CC14  | CC16  |     |      |     |      |      |      |
| 95.0       | CC10  | CC14  | CC16  | CC18  |     |      |     |      |      |      |
| 120.0      | CC11  | CC16  | CC18  | CC20  |     |      |     |      |      |      |
| 150.0      | CC12  | CC18  | CC20  | TCC9  |     |      |     |      |      |      |
| 185.0      | CC14  | CC20  | TCC9  | TCC10 |     |      |     |      |      |      |
| 240.0      | CC14  | TCC9  | TCC10 | TCC11 |     |      |     |      |      |      |
| 300.0      | CC16  | TCC9  | TCC10 | TCC12 |     |      |     |      |      |      |
| 400.0      | CC18  | TCC10 | TCC11 | TCC14 |     |      |     |      |      |      |
| 500.0      | CC18  |       |       |       |     |      |     |      |      |      |
| 630.0      | CC20  |       |       |       |     |      |     |      |      |      |
| 800.0      | TCC9  |       |       |       |     |      |     |      |      |      |
| 1000.0     | TCC10 |       |       |       |     |      |     |      |      |      |

## Single Fixing Cleats

| Part No. | Max mm | Cable Ø inches | Bolt holes | Pack qty |
|----------|--------|----------------|------------|----------|
| CC5      | 12.7   | 0.5            | 6mm        | 100      |
| CC6      | 15.2   | 0.6            | 6mm        | 100      |
| CC7      | 17.8   | 0.7            | 6mm        | 100      |
| CC8      | 20.3   | 0.8            | 6mm        | 100      |
| CC9      | 22.8   | 0.9            | 6mm        | 100      |
| CC10     | 25.4   | 1.0            | 6mm        | 100      |

| Part No. | Max mm | Cable Ø inches | Bolt holes | Pack qty |
|----------|--------|----------------|------------|----------|
| CC11     | 27.7   | 1.1            | 6mm        | 100      |
| CC12     | 30.5   | 1.2            | 10mm       | 50       |
| CC14     | 35.5   | 1.4            | 10mm       | 50       |
| CC16     | 40.6   | 1.6            | 10mm       | 50       |
| CC18     | 45.7   | 1.8            | 10mm       | 50       |
| CC20     | 50.8   | 2.0            | 10mm       | 50       |