

Support & Downloads

PT-E300



[Not your product?](#)

[FAQs & Troubleshooting](#)

[Manuals](#)

[Consumables & Accessories](#)

[Specification](#)

United
Kingdom(English)



[Change Country \(Language\)](#)

PT-E300

Specification

[Contact Us](#)

[Product Registration](#)

[Visit \[www.brother.co.uk\]\(http://www.brother.co.uk\)](#)

Display

Character display	16 characters x 2 guidance and 2 lines text (128 x 56 dot)
Screen contrast	5 levels (+2, +1, 0, -1, -2)

Printing

Print method	Thermal Transfer
Print head	112 dot / 180 dpi
Print height	15.8 mm max. (when using 18 mm tape)
Print speed	Approx. 20 mm / sec.
Tape cassette	Standard TZe tape cassette (3.5 mm, 6 mm, 9 mm, 12 mm, 18 mm widths) Brother HGe tape cassette (6 mm, 9 mm, 12 mm, 18 mm widths)
No. of lines	18 mm tape: 1 - 5 lines; 12 mm tape: 1 - 3 lines; 9 mm tape: 1 - 2 lines; 6 mm tape: 1 - 2 lines; 3.5 mm tape: 1 line

Memory

Memory buffer size	Maximum 2400 characters
File storage	Maximum 50 files

Power Supply

Power supply	Six "AA" alkaline batteries (LR6), Six "AA" Ni-MH rechargeable batteries (HR6), Li-ion Battery (BA-E001), AC adapter(AD-E001)
Auto Power-off	Battery: 5 min. AC adapter: 5 min

Size

Dimensions	Approx. 134 mm (W) x 221 mm (D) x 69 mm (H)
Weight	Approx. 750g (without tape cassette and batteries)

Other

Operating temperature / humidity	10-35 °C / 20-80% humidity (without condensation) Maximum wet bulb temperature: 27 °C
----------------------------------	--