

Internal CW1308

Application

Internal connection of telecom equipment & door entry systems.

Construction

Conductor	0.5mm Solid Copper
Insulation	Colour Coded PVC

Technical

Max Resistance at 20 C	96 Ω /km
Max Capacitance Un-Balanced	500pF/500m
Temperature Rating	+70°C



Part Code	Pairs	Sheath	Colour	100m	200m	Cut to length
SFX/CW1308-2-LSF-WHT	2	LSF	White	✓	✗	✗
SFX/CW1308-3-LSF-WHT	3	LSF	White	✓	✓	✗
SFX/CW1308-4-LSF-WHT	4	LSF	White	✓	✓	✗
SFX/CW1308-6-LSF-WHT	6	LSF	White	✓	✓	✗
SFX/CW1308-10-LSF-WHT	10	LSF	White	✓	✓	✗
SFX/CW1308-20-LSF-WHT	20	LSF	White	✓	✓	✓
SFX/CW1308-50-LSF-WHT	50	LSF	White	✓	✓	✓
SFX/CW1308-100-LSF-WHT	100	LSF	White	✓	✓	✓

Black Available

BUDGET TELECOM

Application

Lower grade installations of telecom equipment & door entry systems

Construction

Conductor	CCA (Copper Coated Aluminium)
Insulation	Colour Coded PVC



Part Code	Pairs	Sheath	Colour	100m
SFX/TC-2-PVC-WHT	2	PVC	White	✓
SFX/TC-3-PVC-WHT	3	PVC	White	✓
SFX/TC-4-PVC-WHT	4	PVC	White	✓
SFX/TC-6-PVC-WHT	6	PVC	White	✓