Aura Smart















Key Features

- Two speed axial fan
- Flow rate up to 133 m³/hr
- Interchangeable spigots 100/125mm
- Modern compact styling optional front covers to match décor
- Quick and easy to fit
- A separate remote controller
- Versatile positioning portrait or landscape
- Exceptionally quiet 21 dB(A)
- Energy efficient low watt motor 3.8W
- Advanced controls for ultimate user comfort
- Universal voltage 100/240v 50/60Hz
- IP44 rating
- Complies with Building Regulations
- 5 year warranty

Aura Smart

The Aura Smart is an innovative low energy axial fan with a unique design for ease of installation and maintenance. The fan is extra slim and with optional colour covers available, it will blend perfectly into the décor of any room. The fan is suitable for mounting anywhere outside of Zone 2 of your wetroom.

The fan comes with interchangeable spigots giving the user the option to use 100mm or 125mm ducting and increase the flow rate accordingly.

This smart fan is available with either humidity timer control or motion sensor humidity timer control giving the user the benefit of achieving the perfect micro climate within their home. Aura Smart has a one-touch control panel beneath the cover for control of the fan. A separate remote controller is also included for convenient control of all the functions - it's a Smart Fan!

Interval ventilation occurs automatically every 15 hours for a period of 2 hours - this ensures regular movement of the air and keeps the room fresh.





Models

Humidity Timer Humidity sensor activates fan - if humidity rises by less than 20% within 10 minutes, run on time reverts to 15 minutes instead of the preset rates of 30, 45 or 60 minutes

Motion Sensor PIR sensor activates fan to switch on - overrun timer Humidity Timer kicks in - can be set at 5, 15 or 30 minutes. If humidity sensor activates the fan - run on time, to clear humidity can be set at 30, 45 or 60 minutes. If the humidity rises by less than 20% in 10 minutes the overrun time will revert to 15 minutes.




Technical Data

Specification	Aura Smart HT		Aura Smart MSHT	
Spigot size	100mm	125mm	100mm	125mm
Air flow m³/hr*	72 / 106	83 / 133	72 / 106	83 / 133
Air flow l/sec*	20 / 29	23 / 37	20 / 29	23 / 37
Fan type	Axial		Axial	
Controls	Humidity Timer		Motion Sensor Humidity Timer	
Mounting	Wall		Wall	
Sound pressure dB(A)@3m	22 / 31	21 / 32	22 / 31	21 / 32
Adjustable delay start (min)	0, 2, 5		0, 2, 5	
Adjustable timer (min)	5, 15, 30		5, 15, 30	
Adjustable timer on humidity activation (min)	30, 45, 60		30, 45, 60	
Interval timer, auto start (hrs)	15		15	
Power watts	Up to 3.8		Up to 3.8	
Specific Fan Power (SFP)	0.13	0.1	0.13	0.1
Building Regulations ADF	Yes		Yes	
Voltage	100-240V/50-60Hz		100-240V/50-60Hz	
Rating	IP44		IP44	
Weight (Kg)	0.63		0.63	
Dimensions (H x W x D)mm	206x152x86		206x152x86	
Part No.	90000384		90000385	


		_			
нт	Colou	ır	MSHT		
90000386	Marble		90000416		
90000387	Silve	r	90000417		
90000388	Champa	gne	90000418		
90000389	Red		90000419		
90000390	Mauve		90000420		
90000391	Graphite		90000421		
90000392	Black		90000422		
Marble	Silver Ch	nampa	agne Red		
Marble Silver Champagne Red					
Mauve G	raphite	Blac	k		
Air flow at fre	e discharç	ge			

Dimensions (mm)



Model	Α	В	С	D	Е
Aura Smart	206	100/125	152	57	29

Performance



Controls and Accessories

A range of accessories including flexible and rigid ducting kits, controls, switches and grilles are available.

See accessories for more details.

















14

