

Electrak® 30 2P + E busbar / buscom trunking

power and communication distribution

CCA3245C

CCA2245C



DDE408C



DDE408



DDE408F



Selection chart (p. 50-51)


Dimensions and technical information (p. 66-71)

Integral communication bus suitable for KNX, Lonworks, DALI protocols, etc. 25 A and 40 A systems

Outlets on one or two sides. IP 4X or IP 54 ingress protection

Fast installation (trunking push fits together in seconds). High quality materials. Suspended or surface mounted

Pack	Cat. Nos.	Electrak 30 2 pole + earth – double sided system		
		2P + E busbar trunking system available in IP 4X and IP 54 versions, with or without integral communications bus circuit Socket outlets are colour coded white and are located on just one side of the bar		
		2P + E trunking lengths		
		Trunking lengths push fit into each other, and feed units or flexible lengths. Double sided trunking must be fixed using suspended fixing brackets		
	25 A	Length (m)	Tap-off outlets	Weight (kg) ⁽¹⁾
1	BBA3245C	3	11	4.85
1	BBA2245C	2	7	3.52
1	BBA3241C	3	6	4.70
1	BBA2241C	2	4	3.47
	40 A	Length (m)	Tap-off outlets	Weight (kg) ⁽¹⁾
1	CCA3245C	3	11	5.05
1	CCA2245C	2	7	3.65
1	CCA3241C	3	6	4.96
1	CCA2241C	2	4	3.61



Pack	Cat. Nos.	Tap-off units		
		16 A unfused tap-off units		
		Pre-wired tap-off units to pick-up L1+N, colour coded white, can plug into any tap-off outlet		
		Length (m)	Fixed polarity	Weight (kg) ⁽¹⁾
1	DDE408C	0.8	L + N	0.2
1	DDE42C	2		0.4
1	DDE43C	3		0.5
1	DDE45C	5		0.7
		13 A fused tap-off units		
		Pre-wired tap-off units to pick-up L1+N, supplied with BS 1362 fuse, colour coded white, can plug into any tap-off outlet		
		Length (m)	Fixed polarity	Weight (kg) ⁽¹⁾
1	DDE408FC	0.8	L + N	0.2
1	DDE42FC	2		0.4
1	DDE43FC	3		0.5
1	DDE45FC	5		0.7

		Feed units for double sided system		
		Double sided feed units come with 2 x 25 mm Ø cable entry holes for each side. Single screw cable terminals are provided for power and also data for buscom varieties		
		Suspended		
		Length (m)	Weight (kg) ⁽¹⁾	
1	BBA24LFC	25 A left	1.29	
1	BBA24RFC	25 A right	1.51	
1	CCA24LFC	40 A left	1.39	
1	CCA24RFC	40 A right	1.61	

		Tap-off units – rewirable		
		16 A unfused tap-off unit		
		Pre-wired tap-off units to pick-up L1+N, colour coded white, can plug into any tap-off outlet		
		Fixed polarity	Weight (kg) ⁽¹⁾	
1	DDF4	L + N	0.14	
		13 A fused tap-off unit		
		Pre-wired tap-off units to pick-up L1+N, supplied with BS 1362 fuse, colour coded white, can plug into any tap-off outlet		
		Fixed polarity	Weight (kg) ⁽¹⁾	
1	DDF4	L + N	0.14	

		Flexible lengths for double sided system		
		Flexible lengths can be used to change direction, change level or overcome obstructions		
		Suspended – right to left		
		Length (m)	Tap-off outlets	Weight (kg) ⁽¹⁾
1	BBA240XC	0.5	25	3.14
1	BBA242XC	2	25	3.67
1	CCA240XC	0.5	40	3.25
1	CCA242XC	2	40	3.91

(1) Weights shown are for IP 4X rated buscom. For all other weights, contact us on +44 (0) 845 600 6266

Key : How to select the correct components

All examples on this page show IP 4X buscom trunking

IP rating and trunking type is dictated by the red letters

4 = IP 4X. For IP 54 version, replace 4 with 5

C = Buscom (with communications circuit). For busbar (power only), remove the C