

Model. PCMINI

Mini Photocell - Thermal Switching

Features & Benefits

- Dust and low pressure water tight
- Dusk to dawn procedure with Thermal Photodiode

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

This dusk and dawn wall mounted mini photocell sensor is designed for automatic lighting fittings control. It combines the latest sensor technology and modern design to create a well-balanced unit. It is IP65 rated for outdoor or indoor use. The photocell comes with a switching delay function and adjustable LUX control.

Technical Specifications

General Information

Product Colour / Finish	Black
Dimensions - (mm)	40x51x26mm
Cut-Hole - Ø (mm)	n/a
Ingress Protection (IP)	IP65

Electrical

Wattage - (W)	2000W
Frequency - (Hz)	50/60Hz
Power source	Mains 220-240v
Detection Distance	n/a
Ambient Light	40° to 70°
Time Delay	n/a
Detection Range	Min 20lux, max. 80lux
Detection Motion Speed	n/a
Installation Height	17mm

Performance Data

Specifications	BSEN60730-1
Approvals / Accreditations	CE, RoHS
Relay Rating	n/a

Construction

Body Material	Enclosure and lens made from polycarbonate
Weight	n/a
Warranty Years	1Yr

Others

Applications	Domestic and commercial applications
--------------	--------------------------------------

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE