

# MS double sided busbar

## tap-offs and accessories



51515056



51515058



51500161



Tap-offs can be supplied pre-wired and fitted with protective devices

Contact us on +44 (0) 845 600 6266



51515052



51500160



51515051



Dimensions and technical information p. 25-26

Tap-off boxes can be used to connect and energise one and three phase loads up to 63 A. Tap-offs can be inserted and removed when the busbar is energised and when the fixture is under load, up to a capacity 32 A. Compliant with IEC 60695-2-10 with V1 self-extinguishing degree (UL 94) Standard IP 55 degree of protection

Pack	Cat. Nos.	Tap-off boxes IP 55	Pack	Cat. Nos.	Tap-off boxes with isolating device on the cover
1	51515071	Energy withstand 400·10 <sup>3</sup> A <sup>2</sup> S Totally insulated tap-off box Max. cable size 25 mm <sup>2</sup> <b>Max. power losses 10 W</b> Empty tap-off box with DIN (4 mod.) Rating (A)   Weight (kg) 32   0·68 Tap-off box with CH10 fuseholder (10·3 x 38) Rating (A)   Weight (kg) 32   0·68	1	51515051	<b>Tap-off box with CH10 fuseholder (10·3 x 38)</b> 10·3 x 38 fuses not included Rating (A)   Weight (kg) 16   0·908
1	51515076	Tap-off box with D01 fuseholder Rating (A)   Weight (kg) 32   0·68	1	51515052	<b>Tap-off box with CH14 fuseholder (14 x 51)</b> 14 x 51 fuses not included Rating (A)   Weight (kg) 50   0·908
1	51515077	Tap-off box with D02 fuseholder Rating (A)   Weight (kg) 16   0·95	1	51515057	<b>63 A tap-off boxes</b> Energy withstand 400·10 <sup>3</sup> A <sup>2</sup> S MAX power losses 20W Tap-off box with transparent cover Weight 1·1 kg
1	51515078	Tap-off box with D02 fuseholder Rating (A)   Weight (kg) 32   0·95	1	51515056	Tap-off box with transparent cover and hinged door (up to 4 mod.) Weight 1·2 kg
1	51515072	Tap-off box for (4 mod.) DIN Rating (A)   Weight (kg) 32   0·73	1	51515067	Tap-off box with hinged door (up to 7 mod.) Weight 1·1 kg
1	51515073	<b>Max. power losses 16 W</b> Empty tap-off box (8 mod.) Rating (A)   Weight (kg) 32   0·93	1	51515058	<b>Tap-off box with hinged door (up to 16 mod.)</b> Energy withstand 400·10 <sup>3</sup> A <sup>2</sup> S MAX power losses 20W Weight 2·5 kg
1	51515074	Tap-off box (4 mod) DIN (long version) Rating (A)   Weight (kg) 32   0·96			<b>Accessories</b>
1	51515075	Tap-off box (8 mod) DIN (long version) Rating (A)   Weight (kg) 32   0·99	1	51501351	<b>End cover IP 55</b> End covers are fitted to the last length in each run to maintain IP 55 protection Weight 0·57 kg
			1	51500161	<b>Joint cover IP 55</b> One for each joint Weight 0·788 kg
			1	51500160	<b>Tap-off outlet cover IP 55</b> 6 per 3 m straight length Weight 0·061 kg
			1	51002002	<b>Suspension bracket</b> Universal fixing brackets enable trunking to be either suspended or wall mounted 1 per 2 m Weight 0·1 kg