Metal clad

Common characteristics

• Dimensions: 79 x 79 x 42 mm (1 gang), 79 x 139 x 42 mm (2 gang)

13 A socket-outlet



• BS 1363

Cat. no.		Gang	Description	Qty
Grey	Silver grey			
GMC131S	GMCS131S	1	unswitched	10
GMC132S	GMCS132S	2	unswitched	5
GMC131SS	GMCS131SS	1	switched	10
GMC132SS	GMCS132SS	2	switched	5
GMC51S	GMCS51S	1	5 A round pin unswitched	10

13 A DP outboard rocker switched socket-outlet

•BS 1363

● DO 1000				
Cat. no.		Gang	Description	Qty
Grey	Silver grey			
GU3630GMC	GU3630GMCS	2	switched	1
GU3631GMC	GU3631GMCS	2	switched with clean earth	1
GU3632GMC	GU3632GMCS	2	switched red with rockers, clean earth and neons	1
GU3633GMC	GU3633GMCS	2	switched with clean earth and non standard	1
GU3634GMC	GU3634GMCS	2	switched with red rockers, clean earth, non standard and neons	1
GU3634GMC25	GU3634GMCS25	2	switched with red rockers, clean earth, non standard and neons*	1

^{*2} gang box includes 5 x 20 mm & 3 x 25 mm knockouts

30mA RCD protected devices



• BS 7288 • BS 7288/BS 5733

Cat. no.	Gang	Description	Qty
LMCSKT1GR	1	Active control socket-outlet*	1
LMCSKT2GR	2	Active control socket-outlet*	1
LMCSKT2GRP	2	Passive control socket-outlet**	1
GMCPRCDSKT1G	1	Passive control switched socket- outlet **	1
GMCPRCDSKT2G	2	Passive control switched socket- outlet**	
GMCPRCDFCU	1	Passive control fused connection unit**	1

^{*} Electronic latch/Active control - device will fail safe in the event of loss of supply. Suitable for domestic use.



GMCS131S



LMCSKT2GR



GMCPRCDSKT1G



GMCPRCDFCU

Note: All products except grid plates are supplied complete with 42 mm depth surface mounting box in matching finish. 1 gang box includes 4 x 20 mm knockouts, 2 gang box includes 10 x 20 mm knockouts

^{**} Mechanical latch/Passive control - device will only trip in the event of a fault. Suitable for freezers and commercial applications.