

Common characteristics

- Dimensions: 86 x 86 mm
- Fix Screws: M3.5 x 30 mm



GU6022LV



GU2014WH



GU2003



GU5000

Low voltage dimmer switches



- BS EN 60669-2-1

Cat. no.	Gang	Description	Qty
GU6011LV	1	1 way 400 VA rotary	1
GU6012LV	1	2 way 400 VA push	1
GU6022LV	2	2 way 250 VA push	1
GU6032LV	3	2 way 250 VA push	1
GU6042LV	4	2 way 250 VA push	1

20 AX & 32 A DP switches and flex outlet plates



- BS EN 60669-1

Cat. no.	Description	Qty
GU2010	20 A DP	10
GU2011	20 A DP with neon	10
GU2013	20 A DP with flex outlet	10
GU2014	20 A DP with neon and flex outlet	10
GU2014WH	20 A DP with flex outlet and neon marked water heater	10
GU4031	32 A with neon	10



- BS 5733

Cat. no.	Description	Qty
GU2033	25 A side entry flex outlet plate	10
GU2003	20 A front entry flex outlet plate	10

13 A unswitched fused connection units



- BS 1363

Cat. no.	Description	Qty
GU5000	13 A unswitched	10
GU5000RD	13 A unswitched - red	10
GU5001	13 A unswitched with neon	10
GU5003	13 A unswitched with flex outlet	10
GU5004	13 A unswitched with neon & flex outlet	10
GU50003	3 A unswitched	10
GU50033	3 A unswitched with flex outlet	10