






Inspiration starts here PRODUCT SELECTOR

EURO POWER MODULES	EURO DATACOM MODULES			
USB CHARGING 2 MODULE 50 X 50MM	RJ11/12 1 MODULE 25 X 50MM	RJ45 CAT 6 1 MODULE 25 X 50MM	RJ45 CAT 6 SCREENED 1 MODULE 25 X 50MM	RJ45 CAT 6 ANGLED 1 MODULE 25 X 50MM
				

FUNCTIONAL MODULES					
White	K5837WHI	K5887WHI	K5846WHI	K5846SWHI	K5864WHI
Black	K5837BLK	K5887BLK	K5846BLK	K5846SBLK	

USB charging sockets, each capable of supporting 2A charge (total of 2A)
K5837 MOUNTING BOX
 35mm minimum
 46mm for extra wiring space
 IEC 60950-1
 IEC 61000-6-1/3

Suitable for both RJ11 and RJ12 jacks
 RJ11: 4 wire
 RJ12: 6 wire
MOUNTING BOXES
 Minimum box depth 35mm
 FCC68
 EN 41003

Cat 6 performance.
 Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES
 Minimum Box Depth 35mm
 ISO/IEC 11801
 EN 50173
 TIA 568
 EN 41003

Cat 6 performance.
 Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES
 Minimum Box Depth 35mm
 ISO/IEC 11801
 EN 50173
 TIA 568
 EN 41003

Cat 6 performance.
 Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES
 Minimum Box Depth 35mm
 ISO/IEC 11801
 EN 50173
 TIA 568
 EN 41003

Mains operated products and extra low voltage modules must not be installed within the same frontplate.
 Refer to BS 7671:2008 for details.