



Energy saving pendant



Cat. no.	Description	Qty
GESPEND613	13 W Energy saving pendant with 6" flex	1
GESPEND618	18 W Energy saving pendant with 6" flex	1

- Requires:
1 x 13 W 4 pin compact fluorescent lamp (not supplied) or
1 x 18 W 4 pin compact fluorescent lamp (not supplied)



GBATS

Safety ceiling accessories



- BS EN 61184
- BS 7895

Cat. no.	Description	Qty
GBATS	Pre-wired safety batten lamp holder	10
GPEND6S	6" safety pendant lamp holder	10
GLHCS	Safety lamp holder with integral cord grip	10

- Mains supply is disconnected until lamp is fully inserted.
- DP switching mechanism for complete isolation
- Terminals can only be accessed via tool



GSWPULL45N

Ceiling switches



- BS EN 60669-1

Cat. no.	Description	Qty
GSWPULL6	6 AX 1 way	10
GSWPULL62	6 AX 2 way	10
GSWPULL45	45 A double pole 1 way	10
GSWPULL45N	45 A double pole 1 way with neon	10

- All items have 1.5 m white nylon cord
- GSWPULL6 and GSWPULL62 fit BESA boxes with standard 50.8 mm centre distances between the fixings
- Fully rated at 6 AX for fluorescent or inductive loads