

Common characteristics

- Dimensions: 86 x 86 mm (1 gang), 86 x 146 mm (2 gang)
- Fix screws: M3.5 x 30 mm



GU3050



GU3021



GU3010D



GU3030

13 A unswitched socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3050	1	unswitched	10
GU3060	2	unswitched	5
GU3060RD	2	unswitched	5

13 A switched socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3010	1	switched	10
GU3020	2	switched	5
GU3011	1	switched with neon	10
GU3021	2	switched with neons	5
GU3010D	1	DP switched	10
GU3010DGY	1	DP switched - Grey	10
GU3010DRD	1	DP switched - Red	10
GU3020D	2	DP switched	5

13 A DP outboard rocker switched socket-outlet



- BS 1363 (where applicable)

Cat. no.	Gang	Description	Qty
GU3030	2	switched	5
GU3030GY	2	switched - Grey	5
GU3030RD	2	switched - Red	5
GU3031	2	switched with clean earth	5
GU3032	2	switched red with rockers, clean earth and neons	5
GU3033	2	switched with clean earth and non standard	5
GU3034	2	switched with red rockers, clean earth, non standard and neons	5

Note All 2 gang socket-outlets include twin earth terminals as standard, enabling high integrity earthing. To aid flush installation 35 mm steel boxes are recommended.