

► Ducting Ancillaries

Alongside our ventilation systems and ducting, we offer a range of ancillary items.

Rigid Duct Aluminium Duct Tape – 45m & 100m



Code	Length
50TP45	45m
50TP100	100m

Overview

A 30 Micron soft tempered bright aluminium foil. Coated with high tack pressure adhesive which has excellent UV light resistance on a white glassine liner.

This product is recommended where a moisture barrier and cold weather performance is required.

Technical data	Typical values
Adhesive colour:	Clear
Adhesive type:	Acrylic UV Light resistance
Tape thickness:	0.060mms (without liner)
Foil thickness:	0.030mms
Peel adhesion to steel:	1000N/M
Loop tack:	800N/M
Shear (static):	87 Hours @ 1kg
Fire protection:	Conforms to Class O BS476 part 7 & 6 1987
Minimum applic temp:	0°C
Service range:	-20°C to 120°C
Shelf life:	12 months (PSMA Conditions)

PVC Duct Tape (non flame retardant) – 4.6m & 33m



Code	Length
123-4	4.6m
123	33m

Applications

- Jointing of polythene sheeting
- Barrier tape to prevent electrolytic reaction
- Sealing insulation panels
- Patching, sealing (boxes, drums, kegs) repair

Technical data	Typical values
Total thickness:	0.14 mm
Adhesive power:	200N/m
Backing thickness:	-
Tensile strength:	2KN/m
Elongation:	200%
Temperature:	-20°C to 80°C
Dielectric strength:	6KV
Colours:	Black, White, Grey
Shelf life:	12 months

Warranties

The above figures are average values and should not be regarded as maximum or minimum values for specification purpose.

The purchaser shall be responsible for determining the suitability of this purpose. Goods which prove to be defected through

faulty material or workmanship must be returned to us carriage paid. These will be replaced or credited. We shall not be liable for consequential damage incurred in the use of this material. All slitting and length tolerances are to British Standards, but other tolerances are available by request.