

Aluminium/Polyester Flexible Hose – 3m - 10m



Ø100mm
EasyPipe 100



Free Area 7,850mm²

Ø125mm
EasyPipe 125



Free Area 12,266mm²

Ø150mm
EasyPipe 150



Free Area 17,263mm²

Key benefits

- ▶ Supplied in standard 10 metre length, compressed to 0.6 metre
- ▶ Individually boxed
- ▶ Easy to connect to either round or oval ducting
- ▶ No special tools required for cutting or fixing
- ▶ In the event of a fire, no toxic gases are emitted
- ▶ The products have been successfully fire resistance tested to BS476 parts 6, 7 and 20

Overview

The Aluminium Flexible Hose is a range of fully flexible uninsulated aluminium/polyester laminated ducting, which has been specially designed for Domus Ventilation. Due to its flexibility it is easy to connect to either round or oval ducting.

| Code | Connection |
|-------------------|------------|
| Hose – 3m | |
| 3133 | Female |
| Hose – 6m | |
| 3136 | Female |
| Hose – 10m | |
| 31310 | Female |

| Code | Connection |
|-------------------|------------|
| Hose – 3m | |
| 5133 | Female |
| Hose – 6m | |
| 5136 | Female |
| Hose – 10m | |
| 51310 | Female |

| Code | Connection |
|-------------------|------------|
| Hose – 3m | |
| 6133 | Female |
| Hose – 6m | |
| 6136 | Female |
| Hose – 10m | |
| N/A | N/A |

Technical data

| | |
|--------------------------------|--|
| Construction material | Reinforced Aluminium/Polyester |
| Wirepitch | 24mm |
| Diameter range (mm) | 100 / 125 / 150 |
| Temperature range (°C) | -30/+140 |
| Maximum air velocity | 30m/sec |
| Max. positive working pressure | 2500 Pa |
| Standard length | 10 metre |
| Packing | Individual box of 0.6 metre |
| Clamping | Lightning Band, Stainless Steel Clamps, Nylon Clamps or Quick Release Clamps |

Construction

The Domus Ventilation Aluminium Flexible Hose is multi-ply reinforced aluminium and polyester laminated ducting with an encapsulated high tensile steel wire helix.