

GU3210BSS

Ultimate Flat plate - switched socket - 1 gang - stainless steel



Main

Range of product	Ultimate
Aesthetic name	Flat plate
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Earth circuit	Standard earth
Colour tint	Stainless steel matt Black
Quantity per set	Set of 1

Complementary

Actuator	Rocker
Number of gangs	1 gang
Pilot light	Without neon indicator
Device mounting	Wall mounted
Rated current	13 A 230 V AC 50 Hz
Fixing mode	By screws: M3.5 30 mm
Connections - terminals	Screw terminal
Material	Steel
Height	88 mm
Width	88 mm
Depth	30 mm

Environment

Standards	BS 1363
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.