

# Wonder Gel

Single component insulating gels in cartridge to instantly protect new installations and oversee maintenance of all types of electrical connections

**Installer's best friends**. Electrical connections, within empty enclosures, are exposed to the risk of short circuit, oxidation and corrosion, at times, resulting in irreparable damages. Without stress and no waiting around, WonderGel and WonderGel Invisible make your job easier, guaranteeing the protection and safety of systems in compliance to best practice rules to provide the highest quality solution, quick and perfect to get the satisfaction of both you and your clients.

• Ready to use! No mixing required! Already cross-linked! No need to wait!



• Eliminate annoying out of service instances caused by moisture

• Protect your systems from the penetration of insects

 Protect your electrical connections from oxidation and corrosion

• Italian Utility Model



VIDEO SURVEILLANCE





CONNECTIONS IN MOIST



Time and space-saver

> EASY TO APPLY EVEN IN AREAS WHICH ARE **DIFFICULT TO ACCESS!**

UNDERGROUND CONNECTIONS



GEL



### WHAT IS GEL WONDER?

- A single component gel
- Extremely sticky
- Stays soft with time
- Never dries
- Non-toxic and safe
- No shelf life



#### WHAT DOES GUARANTEE?

- Maximum insulation and sealing
- Effective and stable adhesion with the passing of time
- High resistance to water pressure
- Degree of protection IP68 when dispensed in suitable casings



### WHY IS IT IN A CARTRIDGE?

- Always ready to use and at your fingertips
- Can be used with standard guns
- It is measurable
- No waste
- Complete with nozzle
- Extremely rapid to use even in difficult positions
- Compact







#### Characteristics

- Single component gel which comes already cross-linked in a cartridge
- No mixing, no waiting time
- · Visco-elastic gel which is extremely fluid
- Self-levelling and self-vulcanizing
- Can be applied using standard silicone ratchets
- Easy to measure
- Does not expire and does not harden
- Easy to apply even to inaccessible areas
- Characteristics do not deteriorate with the passing of time
- Re-enterable
- Non-toxic and safe
- Can be applied in all weather conditions, even when raining or in the heat of the summer sun
- Can be applied to powered appliances
- Dielectric strength > 23 kV/mm
- Volume resistivity  $> 2.10^{15} \Omega$  cm
- Operating temperature from -60 / +200°C
- Overload temperature for brief periods: 250°C
- Gel UL 94-HB

<sup>\*</sup> Protection degree IP68 in proper casings





## Wonder Gel

Product	Colour	Package type	Total quantity
Wonder Gel	•	Cartridge with measuring nozzle	280 ml
Wonder Gel Invisible	0	Cartridge with measuring nozzle	280 ml