Product data sheet Characteristics

GU3220DBSS

Ultimate Flat plate - switched socket - 2P - 2 gangs - stainless steel



Main

Range of product	Ultimate
Aesthetic name	Flat plate
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	2P
Outlet standard description	3 pins
Outlet standard	British
Earth circuit	Standard earth
Colour tint	Stainless steel matt Black
Quantity per set	Set of 1

Complementary

Rocker	
2 gangs	
Without neon indicator	
Wall mounted	
13 A 230 V AC 50 Hz	
By screws: M3.5 30 mm	
Screw terminal	
Steel	
88 mm	
148 mm	
30 mm	
	2 gangs Without neon indicator Wall mounted 13 A 230 V AC 50 Hz By screws: M3.5 30 mm Screw terminal Steel 88 mm 148 mm

Environment

Environment		
Standards	BS 1363	
IP degree of protection	IP20	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherened for and is not to be used for determining suitability or inherened specific user applications. It is the documentation is not integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.