

716SERIES

150kg MAX. LOAD
(Load includes user, tools, materials, etc.)

Fibreglass Stepladders



EN131



COMPATIBLE
SEE PAGES 11-12

Fully compatible with unique Werner Lock-In System to customise the ladder top (See page 11-12)

Non-conductive fibreglass stiles, ideal for working around electricity

Slip-resistant treads

Generous 298mm tread pitch gives excellent working heights

Holster Top with specially designed tool and equipment holders

Semi-tubular rivets provide rigid fixings

H-spreader enables single handed operation and add to the strength and stability of the ladder

EDGE moulded brace and foot pad combination provides enhanced bracing strength and protects the base tread from damage



The Lock-In Accessory System lets you customise the ladder top and safely secure your tools



EDGE bracing provides enhanced strength and increased protection against damage

Suitable for Professional & Non-Professional use

SPECIFICATIONS

| Style | Product Code | No. of Treads | Open Height | Safe Working Height* | Weight |
|-----------|--------------|---------------|--------------|----------------------|---------|
| Swingback | 7160418 | 4 | 1.12m (3'8") | 2.04m (6'8") | 6.79kg |
| | 7160518 | 5 | 1.40m (4'7") | 2.32m (7'7") | 7.70kg |
| | 7160618 | 6 | 1.67m (5'6") | 2.59m (8'6") | 8.80kg |
| | 7160818 | 8 | 2.23m (7'4") | 3.15m (10'4") | 11.60kg |
| | 7161018 | 10 | 2.79m (9'2") | 3.70m (12'2") | 16.50kg |
| | 7161218 | 12 | 3.34m (11') | 4.26m (14') | 19.60kg |

*Based on 1.75m (5'9") as the average reach height of a person.