



■ For installation guidance see pages 70-90

# Zip HydroTap

## Classic Plus All-in-One

Filtered: <b>Boiling</b> Chilled Sparkling	Filtered: <b>Boiling</b> Chilled	Plus unfiltered: <b>Hot &amp; cold</b>
---	--	---

### Features and benefits

- Convenience and ease - By providing your choice of instant boiling, chilled and sparkling water plus unfiltered hot and cold water all from one tap, the HydroTap Classic Plus All-in-One allows you to replace mixer taps and simplify your kitchen design.
- Advanced filtration - Market leading 0.2 micron MicroPurity™ filtration technology filters out dirt, lead, cysts and microplastics, providing 25 times more effective filtration than a standard water filter jug.
- Environmentally conscious operation - The HydroTap employs water-conserving air-cooled chilling technology with 0% global warming potential R290 refrigerant and energy saving sleep modes for maximum efficiency.
- Unique user-safety options - Designed with safety in mind, the Zip HydroTap features boiling isolation, cool touch tap and safety lock features to enhance the user experience. The boiling point is factory set to 98°C to ensure smooth, safe, non-sputtering water delivery.
- Enhanced hygiene - The 5th generation HydroTap command centre has SteriTouch® embedded in key components of the water path and in the HydroTap Classic Plus All-in-One touchpad. This reduces surface bacteria by 99.99%.
- Power-Pulse™ technology - Minimises power consumption by regulating power during heating and maintains stored boiling water to within 0.2°C of set temperature, meaning water is always dispensed at the desired temperature.
- Vented and mains systems available.
- Cost efficient - Vented systems eliminate the need for a separate hot water supply, saving you space, energy and costs.

### Boiling system

- Open outlet, vented system; factory set to operate at 98°C.
- Adjustable boiling temperature set-point.
- Flow rate 4.0 l/min.

### Chilling system

- Fan-cooled condenser type, factory set to operate at 3-5°C for chilled sparkling products, and 6-10°C for chilled products.
- Chilled flow rate 4.0 l/min.
- Sparkling flow rate 1.6l/min.
- Refrigerant R290.

### Tap operation

- Press and hold red 'boiling' button and safety button simultaneously for boiling water.
- Press and hold blue 'chilled' button for filtered chilled water.
- Press and hold white 'sparkling' button for filtered sparkling water.
- To dispense water hands-free for up to 15 seconds, press 'continuous flow' button followed by your desired water option.

### Mixer flow

The mixer will deliver up to 5l/min.

### Spout

Long reach spout swings through 140° to make washing up easier.

### Installation

- Must comply with current water supply regulations.
- Check installation guidance of required rear clearance for mixer lever

### Finishes


Classic Plus AIO boiling chilled sparkling and boiling and chilled (mains) is available in our bright chrome finish only. Classic Plus AIO boiling chilled (vented) is available in both bright chrome and matt black.



BRIGHT CHROME    MATT BLACK

### Warranty

This product comes with a two year parts and labour and a five year boiling tank warranty.



HydroTap Classic Plus All-in-One can be installed over sink only

Boiling | Chilled | Sparkling  
Mains

Product code	H56760Z00UK	H56761Z00UK	H56762Z00UK	H56763Z00UK
Water options	BCS	BCS	BCS	BCS
Users	20	40	60	100
Boiling cups per hr @ 167ml	100	140	160	240
Chilled or Sparkling glasses per hr @ 200ml	75	75	175	175
Power rating kW @ 230V	2.13	2.13+2.2*	2.3	2.3+2.2*
W x D x H** (mm)	339x483x333	339x483x333	500x520x373	500x520x373

Boiling | Chilled | Sparkling  
Vented

Product code	H58777Z00UK	H58775Z00UK	H58776Z00UK
Water options	BCS	BCS	BCS
Users	40	60	100
Boiling cups per hr @ 167ml	140	160	240
Chilled or Sparkling glasses per hr @ 200ml	75	175	175
Power rating kW @ 230V	2.13+2.2*	2.3	2.3+2.2*
W x D x H** (mm)	339x483x333	500x520x373	500x520x373

Boiling | Chilled  
Mains

Product code	H56702Z00UK	H56799Z00UK	H56704Z00UK	H56705Z00UK
Water options	BC	BC	BC	BC
Users	20	40	60	100
Boiling cups per hr @ 167ml	100	140	160	240
Chilled glasses per hr @ 200ml	75	75	175	175
Power rating kW @ 230V	2.15	2.15+2.2*	2.13	2.13+2.2*
W x D x H** (mm)	280x478x373	280x478x333	500x520x373	500x520x373

Boiling | Chilled  
Vented

Product code	H56726Z00UK	H56723Z00UK	H56724Z00UK
Water options	BC	BC	BC
Users	40	60	100
Boiling cups per hr @ 167ml	140	160	240
Chilled glasses per hr @ 200ml	75	175	175
Power rating kW @ 230V	2.05+2.2*	2.13	2.13+2.2*
W x D x H** (mm)	280x478x373	500x520x373	500x520x373

Chilled and sparkling are a combined output.

\* These Zip HydroTap G5 models are installed with a 2.2kW, externally mounted, booster and must be connected to two separate 13 amp power supplies.

\*\* Dimensions relate to the command centre and include integrated or external ventilation tray where applicable.

Chilled and sparkling are a combined output.

\* These Zip HydroTap G5 models are installed with a 2.2kW, externally mounted, booster and must be connected to two separate 13 amp power supplies.

\*\* Dimensions relate to the command centre and include integrated or external ventilation tray where applicable.