

Stratus LED Surface Luminaires



Description

A slim and elegant range of environmentally friendly, low energy LED light fittings. Suitable for internal or external use. Available in both white and chrome finish.

Features

- Small 8W option available, only 270mm diameter
- 14W Standard 330mm diameter
- White or Chrome bezel with opal diffuser
- Microwave sensor for reliable presence detection
- Emergency option available
- Elegant clean lines with smooth finish
- Slim profile
- Tough Polycarbonate diffuser
- Tough polycarbonate body
- Low power consumption
- Instant illumination
- Zero maintenance
- Emergency version uses Tridonic EM LED Driver
- 3 hour duration battery backup (emergency version)
- 3-year Guarantee

Range

8W LED Standard – White	L1011WH
8W LED Standard – Chrome	L1011CH
14W LED Standard – White	L1021WH
14W LED Standard – Chrome	L1021CH
14W LED with Microwave sensor - White	L1022WH
14W LED with Microwave sensor - Chrome	L1022CH
14W LED Emergency version – White	L1023WH
14W LED Emergency version – Chrome	L1023CH

Dimensions

	Diameter	Tilt
8W	270	80
14W	330	80

All dimensions in mm

Technical Specification

Wattage	See range table
Voltage	230-240V 50Hz
Chip type	SMD
Lumen Output	14W 1200lm 8W 520lm
Emergency mode lumen output	75lm
CRI	>80
Colour temperature	4000K
Electrical classification	Class I
IP Rating	IP65

Standards

- BS EN 60598-2-1
- BS EN 60529 (IP Rating)
- EN60 598-1:2008
- EN55015:2006+A1:2007+A2:2009
- EN61547:2009
- EN6100-3-2:2006+A1:2007+A2:2009
- LVD 2006/95/EC