

NSYCRN IP66

Steel enclosures made from a continuous length of sheet steel, double folded at the front, with back welding to the frame. Both, externally and internally protected with polyester epoxy resin grey paint RAL7035 texturized.

- IP66 for one door enclosures
- IP55 for two door enclosures
- Series NSYCRN...NSYCRN/T with transparent security glass door.
- Welded studs on the back for direct fixing of mounting plate or other accessories.
- Perforated door reinforcement profiles allowing fixing of equipment.
- Concealed and easily removable hinges allowing over 120° door opening.
- Foamed-in polyurethane gasket and front rain gutter ensures high degree of protection.
- Accessories not included as standard supply.



Enclosures					
Height (A)	Width (B)	Depth (C)	Reference	Weight (Kg)*	Reference with Transparent Door
200	200	150	NSYCRN22150	2.5	-
200	300	150	NSYCRN23150	3.9	-
250	200	150	NSYCRN252150	2.9	-
300	250	150	NSYCRN325150	4.2	NSYCRN325150T
300	250	200	NSYCRN325200	4.3	NSYCRN325200T
300	450	150	NSYCRN345150	6.7	-
300	300	150	NSYCRN33150	4.2	NSYCRN33150T
300	300	200	NSYCRN33200	4.9	NSYCRN33200T
300	400	200	NSYCRN34200	6	NSYCRN34200T
400	300	150	NSYCRN43150	5.6	NSYCRN43150T
400	300	200	NSYCRN43200	5.8	NSYCRN43200T
400	400	200	NSYCRN44200	8	NSYCRN44200T
400	600	250	NSYCRN46250	10	NSYCRN46250T
400	600	300	NSYCRN46300	11.5	-
500	400	150	NSYCRN54150	7.5	NSYCRN54150T
500	400	200	NSYCRN54200	8.6	NSYCRN54200T
500	400	250	NSYCRN54250	9.5	NSYCRN54250T
500	500	250	NSYCRN55250	11	NSYCRN55250T
600	400	150	NSYCRN64150	8.5	NSYCRN64150T
600	400	200	NSYCRN64200	9.8	NSYCRN64200T
600	400	250	NSYCRN64250	10.8	NSYCRN64250T
600	500	150	NSYCRN65150	10.2	NSYCRN65150T
600	500	200	NSYCRN65200	12	NSYCRN65200T
600	600	250	NSYCRN66250	12.3	NSYCRN66250T
600	600	200	NSYCRN66200	14	-
600	600	250	NSYCRN66250	15	NSYCRN66250T
600	600	300	NSYCRN66300	16.3	NSYCRN66300T
600	800	300	NSYCRN68300	22	NSYCRN68300T
700	500	200	NSYCRN75200	14.3	NSYCRN75200T
700	500	250	NSYCRN75250	15.5	NSYCRN75250T
800	600	200	NSYCRN86200	18.7	NSYCRN86200T
800	600	250	NSYCRN86250	20	NSYCRN86250T
800	600	300	NSYCRN86300	21.5	NSYCRN86300T
800	600	400	NSYCRN86400	27	NSYCRN86400T
800	800	200	NSYCRN88200	26	NSYCRN88200T
800	800	300	NSYCRN88300	30	NSYCRN88300T
800	1000	300	NSYCRN810300 **	33	-
800	1200	300	NSYCRN812300D	40	-
1000	600	250	NSYCRN106250	27	NSYCRN106250T
1000	600	300	NSYCRN106300	28	NSYCRN106300T
1000	600	400	NSYCRNG106400	36	NSYCRNG106400T
1000	800	250	NSYCRN108250	34.5	NSYCRN108250T
1000	800	300	NSYCRN108300	35	NSYCRN108300T
1000	800	400	NSYCRN108400	43	NSYCRN108400T
1000	1000	300	NSYCRN1010300 **	46.7	NSYCRN1010300T
1000	1200	300	NSYCRN1012300 **	54	NSYCRN1012300T
1000	1200	400	NSYCRNG1012400D	60	-
1200	600	300	NSYCRNG126300	37	NSYCRNG126300T
1200	600	400	NSYCRNG126400	42	NSYCRNG126400T
1200	800	300	NSYCRN128300 **	44.8	NSYCRN128300T
1200	800	400	NSYCRN128400	50	NSYCRN128400T
1200	1000	300	NSYCRN1210300 **	53.4	-
1200	1000	400	NSYCRN1210400 **	60	-
1200	1200	300	NSYCRNG1212300D	64	-
1200	1200	400	NSYCRNG1212400D	90	-
1400	1000	300	NSYCRNG1410300D	80	-

** Enclosure with 3 point lock
** IP55 Rated