



Switch Disconnectors Double Pole

TWO MODULE

PART NO.	DESCRIPTION
H5500s	100A 230V
H5560s	63A 230V
DIMENSIONS:	CABLE CAPACITY:
83 x 36 x 76mm	50mm ²



MCBs Single Pole

TYPE B CURVE ONE MODULE

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
H5903s	3A 230V	H5932s	32A 230V
H5906s	6A 230V	H5940s	40A 230V
H5910s	10A 230V	H5945s	45A 230V
H5916s	16A 230V	H5950s	50A 230V
H5920s	20A 230V	H5963s	63A 230V
H5925s	25A 230V		



Surge Device

PART NO.	DESCRIPTION
H6820s	TYPE 2 SURGE DEVICE
H6820s-1	NEUTRAL REPLACEMENT CARTRIDGE
H6820s-2	LINE REPLACEMENT CARTRIDGE
DIMENSIONS:	CABLE CAPACITY:
83 x 36 x 76mm	25mm ²



TYPE C CURVE ONE MODULE

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
H8703s	3A 230V	H8725s	25A 230V
H8706s	6A 230V	H8732s	32A 230V
H8710s	10 230V	H8740s	40A 230V
H8716s	16A 230V	H8750s	50A 230V
H8720s	20A 230V	H8763s	63A 230V

Suitable for installation in MK Sentry Consumer Units.
Positive contact status indication.

DIMENSIONS:	CABLE CAPACITY:	SHORT-CIRCUIT BREAKING CAPACITY:
83 x 18 x 79mm	25mm ²	6KA

