



520



522



523



660



722



723



100



060



061

Ingot Fan Isolation Switch

520 10A Ingot 3 Pole Fan Isolation Plate Switch
This product is not modular

Lockable Switches

660 20A Double Pole Key Lockable Switch

Ingot 20A Control Switches With Optional Flex Outlet

522 20A Ingot DP Switch
523 20A Ingot DP Switch With Neon

Ingot 20A Control Switches Without Flex Outlet

722 20A Ingot DP Switch
723 20A Ingot DP Switch With Neon
3 pole and 20A DP switches are non-modular

Blank Plates

060 1 Gang Blank Plate
061 2 Gang Blank Plate

All blank plates supplied with black and white gaskets where applicable.

Dual Voltage Shaver Socket

100 115/230V Dual Voltage Shaver Socket

Click® dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5: 1998 making it safe for use in bathrooms.

Shaver outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet.

Standards: BS EN 60669 660: BS EN 60669-1 Back Box Depth: 35mm Minimum 660: 47mm Minimum
Cable Size: 1 x 2.5mm² / 2 x 1.5mm² 20A: 1 x 10mm² / 4 x 2.5mm² 660: 3 x 2.5mm², 2 x 4mm²
Dimensions: 1 Gang: (88mm x 88mm x 1.3mm*), 2 Gang: (146mm x 88mm x 1.3mm*) *Excluding gasket

Understanding the code:
FP - Plate Style BN - Plate Finish 411 - Product No. BK - Insert Colour.
BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel

Standards: 100: BS EN 61558
Back Box Depth: 100: 47mm min. Cable Size: 100: 2 x 1.5mm² / 1 x 2.5mm²
Dimensions: 1 Gang: (88mm x 88mm x 1.3mm*), 2 Gang: (146mm x 88mm x 1.3mm*) *Excluding gasket

Understanding the code:
FP - Plate Style BN - Plate Finish 411 - Product No. BK - Insert Colour.
BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel