




CCA038



CCA039



CCA605



CCA606



CCA771



CCA780

Switched Socket Outlets

- CCA605** 13A 1 Gang Switched Socket
CCA606 13A 2 Gang Switched Socket

Round Pin Socket Outlets

- CCA038** 5A Round Pin Socket
CCA039 2A Round Pin Socket

Switched Sockets With USB Outlets

- CCA771** 13A 1 Gang Switched Socket With 2.1A USB Outlet
CCA780 13A 2 Gang Switched Socket With 2 X USB Outlets (Total Output 2.1A)

Standards: BS 1363, BS 546 CCA780: BS 5733, BS1363, BS EN 60950-1, EN 61000-6-1/3, EN 61204-3
 Back Box Depth: 25mm Minimum 771: 35mm Cable Size: 4 x 2.5mm² / 2 x 4mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)



CCA050



CCA051



CCA052



CCA053

Fused Connection Units With Optional Flex Outlet Through Front

- CCA050** 13A Fused Connection Unit
CCA051 13A DP Switched Fused Connection Unit
CCA052 13A DP Switched Fused Connection Unit With Neon
CCA053 13A Fused Connection Unit With Neon

Standards: BS 1363 and BS 1362 (fuse)
 Back Box Depth: 25mm Minimum Cable Size: 4 x 2.5mm² / 2 x 4mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)