



140PL



152PL



SP900



MD9014



153PL



154PL



185



186

The dimmer modules are supplied separately to the plates listed above. 140PL, 152PL, 153PL & 154PL are only available in (CH) & (BS) finishes.

**Dimmer Modules**

- MD9001** 6A 2 Way Push On/Off (Non-Dimming) Module (25 x 62mm)
- MD9010** 1-10V Analogue Dimmer Module (25 x 62mm)
- MD9022** 250W 2 Way Dimmer Module (25 x 62mm)
- MD9042** 400W 2 Way Dimmer Module (25 x 62mm)
- MD9014** 100W Dual Mode Dimmer Module with Trim (26.5 x 55mm)

**Dimmer Mounting Unfurnished Plates**

- 140PL** 1 Gang Dimmer Plate & Knob (650W Max) - 1 Aperture
- 152PL** 2 Gang Dimmer Plate & Knobs (800W Max) - 2 Apertures
- 153PL** 3 Gang Dimmer Plate & Knobs (1200W Max) - 3 Apertures
- 154PL** 4 Gang Dimmer Plate & Knobs (1600W Max) - 4 Apertures
- 185** 1 Gang Dimmer Plate & Knob (1000W Max) - 1 Aperture
- 186** 2 Gang Dimmer Plate & Knobs (1630W Max) - 2 Apertures
- SP900** Dimmer M10 Nut Runner Tool

Use the nut runner to easily exchange dimmer modules and create customised dimmer switch plate.

Maximum Wattage: 1 Gang: 1000W, 2 Gang: 1630W  
 Back Box Depth: Up to 400W: 35mm  
 Dimensions: 1 Gang: (88mm x 88mm x 1.3mm\*), 2 Gang: (146mm x 88mm x 1.3mm\*) \*Excluding gasket

Understanding the code:  
 FP - Plate Style BN - Plate Finish 411 - Product No. Please note: Supplied with both black & white gaskets (BN supplied with black gaskets only).  
 BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel



421



MD9125



422



423



424

Brushed Stainless plate finishes require the use of a Pearl Nickel (PN) Toggle Switch Module.

**Toggle Switches**

- 421** 10AX 1 Gang 2 Way Toggle Switch
- 422** 10AX 2 Gang 2 Way Toggle Switch
- 423** 10AX 3 Gang 2 Way Toggle Switch
- 424** 10AX 4 Gang 2 Way Toggle Switch

**10AX Intermediate Toggle Switch Modules**

- MD9125BN** Intermediate Toggle Switch Module - Black Nickel
- MD9125CH** Intermediate Toggle Switch Module - Polished Chrome
- MD9125PN** Intermediate Toggle Switch Module - Pearl Nickel

Not interchangeable with dimmers or other Minigrig™ modules.

Standards: BS EN 60669  
 Back Box Depth: 35mm Minimum Cable Size: 2 x 2.5mm<sup>2</sup> / 4x 1.5mm<sup>2</sup>  
 Dimensions: 1 Gang: (88mm x 88mm x 1.3mm\*), 2 Gang: (146mm x 88mm x 1.3mm\*) \*Excluding gasket

Understanding the code:  
 FP - Plate Style BN - Plate Finish 411 - Product No. Please note: Supplied with both black & white gaskets (BN supplied with black gaskets only).  
 BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel