b30







121 / 126



158 / 065



159 / 066





Twin outlets are 2 separate sockets and are not internally linked together.

RJ11 Telephone Outlet

115 Single RJ11 (Irish/US) Outlet

Telephone Outlets

120 Single Telephone Outlet - Master

121 Twin Telephone Outlet - Master

125 Single Telephone Outlet - Secondary

126 Twin Telephone Outlet - Secondary

Isolated outlets will filter out any interference.

If a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Non-Isolated Coaxial Outlets (Unshielded)

065 Single Coaxial Outlet

066 Twin Coaxial Outlet

Isolated Coaxial Outlets (Unshielded)

158 Single Isolated Coaxial Outlet

159 Twin Isolated Coaxial Outlet

Satellite Outlets (Unshielded) 156 Non-Isolated Single Satellite Outlet

157 Isolated Satellite & Isolated Coaxial Outlet

170 Non-Isolated Satellite & Non-Isolated Coaxial Outlet

Back Box Depth: 16mm Minimum 115: 35mm Minimum Termination Type: IDC Dimensions: 1 Gang: 88mm x 88mm x 8mm

Understanding the code:
DP - Plate Style BN - Plate Finish 536 - Product No. BK - Insert Colour Please note: AB & BN are only available with black inserts.
AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome, BN Black Nickel, SS Stainless Steel.

Back Box Depth: 16mm Minimum
Dimensions: 1 Gang: 88mm x 88mm x 8mm

Understanding the code:

DP - Plate Style BN - Plate Finish 536 - Product No. BK - Insert Colour Please note: AB & BN are only available with black inserts.

AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome, BN Black Nickel, SS Stainless Steel.