



PRW140 / 145



PRW146



SP900



MD9001



PRW147



PRW148

We recommend the use of branded halogen lamps with all Polar™ dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. These dimmer switches have not been designed for use with LED lamps. However, they may be suitable for some good quality LED lamps. For further information please contact the Click® technical support team.

#### Dimmer Modules

- MD9001** 6A 2 Way Push On/Off (Non-Dimming) Module (25 x 62mm)
- MD9010** 1-10V Analogue Dimmer Module (25 x 62mm)
- MD9022** 250W 2 Way Dimmer Module (25 x 62mm)
- MD9042** 400W 2 Way Dimmer Module (25 x 62mm)
- MD9014** 100W Dual Mode Dimmer Module with Trim (26.5 x 55mm)

#### Dimmer Switches

- PRW140** 1 Gang 2 Way 400Va Dimmer Switch
- PRW145** 1 Gang 2 Way 250Va Dimmer Switch
- PRW146** 2 Gang 2 Way 250Va Dimmer Switch
- PRW147** 3 Gang 2 Way 250Va Dimmer Switch
- PRW148** 4 Gang 2 Way 250Va Dimmer Switch
- SP900** Dimmer M10 Nut Runner Tool

Use the nut runner SP900 to easily exchange dimmer modules and create customised dimmer switch plate.

**Standards:** BS EN 60669, BS EN 55015 **Type:** Leading Edge, MD9014: Leading & Trailing Edge  
**Back Box Depth:** 25mm Minimum **Cable Size:** 2 x 1.5mm<sup>2</sup>  
**Dimensions:** 1 Gang: (86mm x 86mm x 11mm), 2 Gang: (146mm x 86mm x 11mm)

## Power Socket Outlets, Fused Connection Units & Control Switches

All socket outlets are tested and approved to BS1363. Socket outlets are available with single or double pole switches. Twin earth terminals are available on 1 and 2 gang socket outlets in order to comply with regulation 607 of BS7671 IEE Wiring Regulations. As with the plate switches, the actual switch rocker features a gentle curved appearance.



13A Wall Socket Outlets | USB Sockets  
 | Round Pin Wall Socket Outlets | Fused Connection Units Fan Isolation Switches | DP Switches

