

PIR Detectors



Order Code	Description
EBDSPIR-DM	D-Mate PIR detector
Supply Voltage	16VDC (via D-Mate bus)
Dimensions	Dia. 76 x 69mm

For detection pattern please see page 19.

Scene Plate



Order Code	Description
DM-SG-4SM-W	D-Mate scene plate
GIFP-ST	Silver effect fascia
GIFP-BZ	Bronze effect fascia
Supply Voltage	16VDC (via D-Mate bus)
Backbox compatibility	UK and EU (minimum depth 25mm)
Dimensions	86 x 86 x 36.5mm

Addressers



Order Code	DM-SL-ADD	DM-SL-ADAR	DM-SL-ADDR
Description	D-Mate addresser DIL DALI/DSI	D-Mate addresser DIL 1–10V relay	D-Mate addresser DIL DALI/DSI relay
Control Output	DALI or DSI (switchable via DIL switch)	1–10V	DALI or DSI (switchable via DIL switch)
Supply Voltage	16VDC (via D-Mate bus)	220–240VAC 50Hz	220–240VAC 50Hz
Relay Rating	—	2A 220–240VAC 50Hz	
Dimensions	20.5 x 22.5 x 184mm		
Maximum 10 ballasts			

Handsets



Order Code	UNLCDHS	UHS5	UHS7
Description	Professional commissioning handset. See page 16	Commissioning handset. See page 15	User handset. See page 15
Battery	6VDC (4 x AAA)	3VDC (1 x CR2025)	3VDC (1 x CR2025)
Dimensions	160 x 36 x 95mm	86 x 4 x 67mm	86 x 4 x 67mm