

Floodlight | XLED home 2 SL

Information copy

Dazzlingly stylish LED floodlight. XLED home 2 SL – the outdoor floodlight without sensor. Freely swivelling LED panel with new opal cover for pleasant wide-area lighting (1184 lm at 14.8 W). Swivelling range: 180° (horizontally and vertically). Cooling system of high thermal conductivity magnesium composite (HCMC). Available in white, black, white, graphite and silver.



Details

14,8w

14,8 W 1184 lm

5 JAHRE
GARANTIE

5 years functional warranty



IP44

LED

30 years (Ø 4,5h / day)



4000K neutral white



networkable via cable



energy saving



Included STEINEL LED-System



HCMC cooling system



UV-protected material



Colour rendering index Ra \geq 80

Technical specifications Floodlight | XLED home 2 SL White

European Article Number (EAN)	4007841033125
-------------------------------	---------------

Dimensions(w x h x d):	181 x 180 x 161 mm
------------------------	--------------------

Voltage	230 - 240 V, 50 Hz/60 Hz
---------	--------------------------

Mains power	75 mA
-------------	-------

Power factor	0.84
--------------	------

Output	14,8 W
--------	--------

Brightness	1184 lm
------------	---------

Efficiency	80 lm/W
------------	---------

Light colour	4000 K / SDCM 3
--------------	-----------------

Colour rendering	Ra \geq 80
------------------	--------------

LED life expectancy	50,000 h (L70B10 to LM80)
---------------------	---------------------------

LED cooling system	HCMC (High Conductive Magnesium Composite)
--------------------	---

Floodlight positioning range	180° horizontally, 180° vertically
------------------------------	------------------------------------

Degree of protection (IP)	IP44
---------------------------	------

Protection class	II
------------------	----

Material	UV-resistant plastic
With lamp	STEINEL LED system
Temperature range	-20°C - +40°C
Lamp replaceable	No
Version	White

Application

under porches, driveways, courtyards, gardens
ideal addition to XLED home 2