

Machine Screws Electrical Range

Steel Countersunk Slot

Socket Screws

- Used with switch and socket boxes
- Raised countersunk type to DIN 964
- Countersunk slot type to DIN 963

- Countersunk slot type suitable for low profile wiring accessories
- Steel
- Bright zinc plated or bright nickel plated
- Supplied in labelled hanging poly bags

Range Information

Product Code	Diameter	Length mm	Unit Qty
Raised Head Countersunk Slot Zinc			
215-400-005	M3.5	25	100
215-400-010		30	100
215-400-015		35	100
215-400-025		40	100
215-400-035		50	100
215-400-040		60	100
215-400-045		75	100
215-400-047		100	100
Countersunk Slot Zinc			
215-500-010	M3.5	50	100

Product Code	Diameter	Length mm	Unit Qty
Raised Head Countersunk Slot Nickel			
215-405-005	M3.5	25	100
215-405-010		30	100
215-405-015		35	100
215-405-020		40	100
215-405-025		50	100
215-405-030		60	100
215-405-035		75	100
215-405-040		100	100



M3.5 Extension Piece

- Solid brass material
- Bright nickel plated
- Suitable for M3.5 machine screws

- Total length 35mm
- Supplied in labelled hanging poly bags

Range Information

Product Code	Diameter	Length mm	Unit Qty
215-365-065	M3.5	35	100



Re-Threaders

Re-Threading Tools

- Made from high speed steel with precision ground threads, taper lead and permanently fitted handle
- Long reach M3.5 version used for deep socket boxes
- Supplied in hanging blister packs

Applications

For cleaning out threads in electrical boxes and other thread restoring applications.

Range Information

Product Code	Size	Length of Shank mm	Unit Qty
218-369-005	M3.5	47	1
218-369-007	M3.5 Long reach	88	1
218-369-010	M4	47	1

