



Nylon Insulation Anchors

Insulation Supports

- Gentle hammer in action
- Disc head allows a good adherence to the render coat
- Shock resisting natural polypropylene material

- Supplied in bags of 100 within boxes of 500

Applications

Suitable for fixing of rigid insulation panels such as polyurethane, polystyrene, cork etc. Particularly suitable for application in concrete and compact base materials.

Range Information

Product Code	Size mm	Hole Diameter mm	Head Diameter mm	Support Length mm	Min. Insert Depth mm	Panel Thickness		Unit Qty
128-325-003	8x50	8	35	50	25	Min. mm	Max. mm	500
128-325-005	8x70	8	35	70	25	20	40	500
128-325-010	8x90	8	35	90	25	50	60	500
128-325-015	8x110	8	35	110	25	70	80	500
128-325-020	8x130	8	35	130	25	90	100	500



Metal Insulation Anchors

Insulation Supports

- Conforms to EN 13501-1:2007/A1:2009
- Fire rated insulation fixing
- Manufactured from pre-galvanised material
- Suitable for fixing of rigid insulation panels
- Can be used in most materials
- Easy to use one piece fixing

- Disc head allows a good adherence to the render coat
- Hole size 8mm
- Hammer in gently
- Tapered end for easy installation
- Supplied in bags of 50 within the box quantities

Range Information

Product Code	Size mm	Hole Diameter mm	Head Diameter mm	Support Length mm	Min. Insert Depth mm	Panel Thickness		Unit Qty
128-325-195	8x60	8	35	60	50	Min. mm	Max. mm	500
128-325-200	8x90	8	35	90	50	10	40	500
128-325-210	8x110	8	35	110	50	30	60	500
128-325-220	8x140	8	35	140	50	50	90	500
128-325-230	8x170	8	35	170	50	80	120	450
128-325-240	8x200	8	35	200	50	110	150	350

Insulation Panel Fixing Washer

128-326-260	35	200
-------------	----	-----

Insulation Fixing Plastic Cover Cap

128-326-270	35	200
-------------	----	-----

Fixing Band



Galvanised

- All purpose flexible fixing band
- Pre punched holes to enable fixing with bolts, screws, nails etc.
- Easy to cut and bend to shape
- Manufactured from galvanised steel

- Flexible yet strong
- Supplied in 10 metre rolls

Applications

Used for securing, supporting and strapping of cables, guttering, fencing, lighting, pipework, trunking and ducting and is ideal for all suspension applications.

Range Information

Product Code	Width mm	Thickness mm	Fixing Hole Diameter mm	Unit Qty	Carton Qty
060-125-005	12	0.7	6.2+3.3	1	20
060-125-010	19	0.7	8.3+3.3	1	10
060-125-015	25	1	8.3+3.3	1	10
060-125-017	50	0.8	4+7	1	8