PRODUCT FEATURES

- Dimensions: 230mm (H) 355mm (W) 115mm
- Cut out dimensions: (L) 335mm (W) 95mm (D) 60mm
- Light source: LED
- Power consumption: 2.1W
- Uses typically 80% less power than that of an 8W fluorescent
- Material: White, brass and chrome
- IP Rating: IP20
- Self test as standard
- Can be switched internally to maintained or non-maintained operation
- Viewing distance: 32m
- Weight: 1.5Kg
- Compliance: BS EN 60598-2-22 and other relevant standards
- Other accessories: Double sided pictograms available



E/CHVL/M3/L/WHST - Vale fitting showing arrow up



	ϵ	F
PRO	DDUC	T CODE






E/CHVL/M3/L/WHST	Vale LED 3 hour maintained white (Self-test complete with legend arrow up
E/CHVL/M3/L/BRST	Vale LED 3 hour maintained brass (Self-test complete with legend arrow up)
E/CHVL/M3/L/CHST	Vale LED 3 hour maintained chrome (Self-test complete with legend arrow up)
ADDITIONAL LEGENDS	
S/LEG/VL/AD	Vale double sided pictograms arrow down legend (insert only)
S/LEG/VL/ALR	Vale double sided arrow pictograms left/right (insert only)
S/LEG/VL/AU	Vale legend arrow up insert pictograms only (insert only)
REPLACEMENT PARTS	
B/BATT/DA/FO/VL/NIHM	Battery for Vale - NiMH

Dale

PRODUCT FEATURES

- Dimensions: 175mm (H) 335mm (W) 38mm (D)
- Light source: LED
- Power consumption: 2.1W
- Uses typically 80% less power than that of an 8W fluorescent
- Material: White mild steel
- IP Rating: IP40
- Self test as standard
- Can be switched internally to maintained or non-maintained operation
- Viewing distance: 32m
- Weight: 1.0Kg
- Compliance: BS EN 60598-2-22 and other relevant standards
- Other accessories: Pictograms available







PRODUCT CODE	DESCRIPTION
E/DA/M3/LED/3/ST	Dale LED 3 hour maintained self-test complete with arrow up legend
ADDITIONAL LEGENDS	
S/LEG/DA/AL/3	Pictogram arrow left
S/LEG/DA/AR/3	Pictogram arrow right
S/LEG/DA/AD/3	Pictogram arrow down
S/LEG/DA/AU/3	Pictogram arrow up
REPLACEMENT PARTS	
B/BATT/DA/FO/VL/NIHM	Battery for dale - NiMH