

Non-metallic conduit systems

PVC Type A & C90 - XF

Type A - XF

Straight fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 / Colour: Black (BL) Only

	Part no.	Nominal conduit size	
		(mm)	Metric thread
	XF12/M16/D	12	M16
	XF16/M16/D	16	M16
	XF16/M20/D	16	M20
	XF20/M20/D	20	M20
	XF25/M25/D	25	M25
	XF32/M32/D	32	M32
	XF40/M40/D	40	M40
	XF50/M50/D	50	M50
For insertion into threaded entries & knockouts. Locknuts supplied with METRIC THREAD ONLY			
To order quote part number, e.g. XF16/M16/D			

Approvals	IP rating	Appropriate conduit	Temperature range
 LOW VOLTAGE DIRECTIVE	For use with: Xtraflex Type XF		Static applications: -5°C to +60°C
	IP40	N/A	Moving applications: -5°C to +60°C
	IP65	Yes	Fitting characteristics
	IP66	N/A	
	IP67	N/A	
	IP68	N/A	
	IP69	N/A	



Type C90 - XF

90° Elbow fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 / Colour: Black (BL) Only

	Part no.	Nominal conduit size	
		(mm)	Metric thread
	XF16/M16/C90	16	M16
	XF20/M20/C90	20	M20
	XF25/M25/C90	25	M25
	XF32/M32/C90	32	M32
For insertion into knockouts. Locknuts supplied with METRIC THREAD ONLY			
To order quote part number, e.g. XF16/M16/C90			

Approvals	IP rating	Appropriate conduit	Temperature range
	For use with: Xtraflex Type XF		Static applications: -5°C to +60°C
	IP40	Yes	Moving applications: -5°C to +60°C
	IP65	N/A	
	IP66	N/A	
	IP67	N/A	
	IP68	N/A	
	IP69	N/A	