



AMALED80/CCT

Matrix LED CCT Linklight 13W



Features

CCT Selectable LED linklight with integral driver

Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options

Moulded spine fitted with integral switch and fixed diffuser

c/w angled and straight fixing clips

Linkable up to a maximum of twelve fittings

LED lifespan L70 25,000 hours

Non-dimmable

Supplied c/w 1.5m mains power cable

Length: 858mm Width: 22.8mm Depth: 38.4mm

General Information

Lamp Type	LED
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Warranty (Years)	2
CE Mark	Yes
Length (mm)	858
Width (mm)	22.8
Depth (mm)	38.4
Accessories	A250TLL/T5, A500TLL/T5, A1000TLL/T5

Technical Information

Wattage	13W
Lumens Delivered	1320lm(Cool White), 1268lm(Warm White)
Lm/W	102lm(Cool White), 98lm(Warm White)
CRI	Ra 80
CCT	4000K/3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C

Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
With light source	Yes
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP20
Protection class	II
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Max. system power	13 W
Colour of light	White
Colour temperature	3000-4000 K
Colour rendering index CRI	80-89
Width	22.8 mm
Height/depth	38.4 mm
Length	858 mm

Datasheet generated from <https://onetimepim.com> last updated Tuesday, June 23, 2020 10:33:07 AM