

#### ATORPLED5/MWS/M3

Tornado Pro 1.5m 29W Integral Microwave Sensor Self-Test Emergency



#### **Features**

Exceeds performance of standard T5 fluorescent.

Ultra slim IP65 LED NCF linear.

Unique base design caters for multiple installation methods.

Installer friendly imbedded features aid accurate and fast installation for any application.

 $\label{thm:continuous} \mbox{Quick release LED array/gear tray assembly provides the installer the means to faster installation/maintenance.}$ 

Fast latching/permanently located stainless steel side clips ensure a quick and secure connection.

Tridonic LED driver as standard.

LED lifespan L80 B10 54,000 hours

Self-test emergency as standard with Li-ion battery technology, reducing charge time and running costs.



Belfast: +44 (0) 2890 773750

### **General Information**

Lamp Type	LED
Emergency	Yes
Self Test	Yes
Integral Microwave Sensor	Yes
IP Rating	IP65
IK Rating	IK07
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface/Suspended
Warranty (Years)	7
CE Mark	Yes
Length (mm)	1565
Width (mm)	85
Height (mm)	70

## **Technical Information**

Wattage	29W
Lumens Delivered	3209lm
Lm/W	111lm
CRI	Ra 80
ССТ	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 40°C



Belfast: +44 (0) 2890 773750




# Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
With light source	Yes
Material housing	Plastic
Colour housing	Grey
Material cover	Plastic, opal
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class	I
Suitable for emergency lighting	Yes
With movement sensor	Yes
With light sensor	No
Max. system power	29 W
Rated luminous flux acc. IEC 62722-2-1	3209 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Luminaire efficacy	111 lm/W
Width	85 mm



Height/depth	70 mm
Length	1565 mm



Datasheet generated from <a href="https://onetimepim.com">https://onetimepim.com</a> last updated Tuesday, June 23, 2020 10:39:17 AM

